

# GENMAC Land TR80 PTO GENERATOR 80,0KVA



Product price:

**6.016,00 € tax excluded**

## Product description:

GENMAC Land TR80 SINGLE/THREE-PHASE GENERATOR 80,0KVA

The generator GENMAC Land TR80 single/three-phase PTO is capable of delivering a power of 80,0KVA with AVR voltage regulator.

The 80,0KVA PTO shaft generator is composed of a frame on which is placed an alternator that can be connected to the tractor by a special speed multiplier on one side, while on the opposite side is equipped with an electrical panel with sockets.

The frame of the 80,0KVA PTO generator has been designed to allow it to operate in the best way without being subject to strong vibrations that can compromise its reliability, in addition it is very simple and practical connection to both the lifting system and the PTO, resulting in a handy use without too much trouble.

The Genmac PTO Generator is driven by means of a gimbal coupling thanks to the P.T.O. action. (Power Take Off) of an agricultural tractor by means of direct coupling to the cardan shaft. Everything is fixed on a sturdy metal frame to protect the alternator and allow a more comfortable use.

The GENMAC PTO shaft generator needs to be connected to a tractor capable of delivering equal to or greater than 247 Hp for correct operation.

## Control panel

The control panel consists of:

- Magnetothermal switch;
- Differential Switch;
- Voltmeter;

- Ammeter;
- Frequency meter;
- Hour Meter;
- 1x schuko, 1x CEE 32A 230V, 1x CEE 125A 400V

### Voltage regulator

The AVR is indispensable to make the generator work at its best, in fact it all needs an electronic control system, which guarantees the good functioning of the machine and of the electrical network behind it.

The purpose of the AVR, in a generator, is to keep the output stable. And if its operation is very simple when resistive loads are fed, more complex is the matter in case of mainly inductive loads: the delayed phase shift current counteracts the inductor magnetic field, causing a voltage drop at the alternator output terminals; to compensate for this phenomenon, it automatically intervenes by increasing the excitation current, until it returns to the nominal value. If the load is capacitive, the current acts as a magnetizer for the inductor causing, and the AVR intervenes by reducing the excitation current.

### TECHNICAL CHARACTERISTICS OF GENERATOR GENMAC Land TR80 80,0KVA

Phase Type: SinglePhase/ThreePhase  
SinglePhase Continuous Power: 26.7 KVA (KW)  
SinglePhase Maximum Power: 29.4 KVA (KW)  
ThreePhase Continuous Power: 80.0 KVA (KW)  
ThreePhase Maximum Power: 88. 0 KVA (KW)  
Alternator RPM: 1500 rpm  
Tractor Power: 247 Hp  
PTO Speed: 400 rpm  
Receptacle Panel: 1 x 32A 230V - 1 x 125A 400V  
Voltage: 230 / 400 V  
Frequency: 50 Hz  
Voltage regulator: AVR  
Degree of protection: IP 23  
Length (mm): 1210  
Width (mm): 975  
Height (mm): 923  
Dry weight (Kg): 362

If you are looking for another product then you can consult other terrestrial generators in our catalog.

Images and technical data are not binding.



**Product features:**

Phase: Single phase / Three phase  
Maximum power single phase (KW): 29.4  
Continuous power single phase (KW): 26.7  
Maximum power single phase (KVA): 29.4  
Continuous power single phase (KVA): 26.7  
Maximum power three phase (KW): 88  
Continuous power three phase (KW): 80  
Maximum power three phase (KVA): 88  
Continuous power three phase (KVA): 80  
Frequency (Hz): 50  
Voltage (V): 230 / 400  
Engine rpm (rpm): 1500  
Oil capacity (L): 2  
Poles: 4  
Protection degree: IP23  
PTO speed (round/min): 400  
Minimum tractor output (HP): 247  
Length (mm): 1210  
Width (mm): 975  
Height (mm): 923  
Dry weight (Kg): 362  
Voltage regulator: AVR

