



HONDA Outboard BF 9,9DK4 SHU

Product price:

2.530,00 € tax excluded

Product description:

HONDA BF9,9DK4 SHU Outboard Engine

The Honda BF9,9DK4 SHU is an outboard engine powerful enough to take you to coastal waters on an inflatable boat or dinghy. Lightweight to carry, they include ergonomic handles and can be easily stored in the trunk of your car.

The Honda BF9,9DK4 SHU has single-cylinder 4-stroke engines with a top valve. They are easy to start with a manual system that allows the outboard to spin freely right away. Honda BF9,9DK4 outboards have the most advanced technology that precisely controls the ignition phase, so when you start it, even in cold weather, it will start without hesitation. The air-cooled BF9,9DK4 provides great maneuverability with 360° rotation and an integrated fuel-saving space tank.

A centrifugal clutch allows the engine to idle without operating the propeller blades. When you want to start moving, just act on the throttle knob, the clutch engages and drives the propeller a bit like it does in an automatic transmission.

It's very important for a small boat to be nimble and able to change direction quickly. The small Honda BF9,9DK4 has a fast turning action, which is perfect for reversing without changing gears. Simply turn the rudder 180° and the boat is able to move in reverse.

Once securely mounted to the boat, you'll find that these outboards are very lightweight and easy to pull out of the water by tilting them. This way you avoid damaging your motor propellers when moving through shallow water or on shore. You can quickly get moving again by operating the spring-loaded system that allows you to lock the motor for safety.

These Honda outboards are the lightest in their class, so it's no wonder they're easy to pull out. They've been made easier to carry, with an ergonomic handle positioned at just the right balance point, allowing you to walk normally without effort.





The sleek design has been taken care of throughout, right down to the slim gearbox that reduces drag in the water while promoting fuel economy.

The knob gives a remarkably smooth feel and is equipped with a screw-clutch that allows it to be locked at various speeds, thus relaxing your hand.

Improving the quality of our lives means, above all, taking care of the environment in which we live. We cannot allow boat fuel to pollute the marine environment. That's why Honda has made outboard engines cleaner, quieter and more environmentally friendly with the introduction of 4-stroke.

First, the aluminum housing is anodized using Honda's patented BF9,9DK4 "double seal" process (1). Then a layer of epoxy primer is applied (2) before silver gloss paint (3). As additional UV protection, a clear resin (4) is applied as a top coat. For added safety, a sacrificial anode is applied to all waterproof connectors.

Technical specifications Honda BF9,9DK4 SHU outboard:

Net Power (kW): 11.2 Net power (Hp): 15 Displacement: 350 cm³ Shank length: Short Dry weight (Kg): 46.5

Starter: Electric / Self recoiling Ignition system: Electronic PGM-IG

Setup and engine lifting: Manual / Manual 5 positions

Transom height (mm): 433

Length (mm): 650 (tiller) / 640 (remote control)

Width (mm): 350 Height (mm): 1110

Bore x stroke: 59 x 64 mm Engine Brand: Honda

Engine Type: OHV, 4 stroke

Number of cylinders: 2

Speed of rotation at full throttle (rpm): 4500-5500

Cooling system: Water (with thermostat)

Are you looking for an outboard with different technical characteristics? HERE you can find the whole range Honda or other brands specializing in the field.

Images are indicative only.

Product features:





Fuel: Gasoline

Engine: OHV, 4 stroke

Ignition: Electronic PGM-IG Starting system: Elettrico Engine capacity (cm³): 350

Number cylinders: 2

Cooling: Water

Bore x stroke (mm): 59 x 64

Reduction ratio: 2,08

Rpm at full throttle (rpm): 4500-5500

Appearance and engine lifting: Manual / Manual 5 position

Transom height (mm): 433

Net power (kW): 11.2

Mechanical power (hp): 15 Fuel tank capacity (L): 12

Length (mm): 650 Width (mm): 350 Height (mm): 1110 Dry weight (Kg): 46.5

Shaft Length: S