



# HONDA Outboard BF150AK2 LCU WHITE Long Shaft 110.3kW

**Product price:**

**11.340,00 € tax excluded**

## **Product description:**

HONDA OUTBOARD BF150AK2 LCU LONG LEG

Honda BF150AK2 LCU are outboard engines perfect for professional use, they are reliable, compact and lightweight complete with PGM-Fi electronic fuel injection system.

Honda BF150AK2 LCU are optimized to offer more power for a wide range of different boats. The decisive, smooth power this advanced technology offers is sure to put a smile on your face as you venture out on the water.

VTEC™ is an efficient system included in the Honda BF150AK2 LCU outboard that keeps fuel consumption down while delivering an exciting increase in power. In the Honda BF150AK2 LCU it works by using two different cams:

- 1) When the outboard is running at low rpm, the valves are operated by a cam less aggressively ensuring low fuel consumption and excellent performance.
- 2) As the outboard speed increases to 5000 rpm, the VTEC™ hydraulically operates a cam with a higher lift profile. This keeps the valves open longer, getting more air into the combustion chamber to produce optimum power, just like in a Formula One race car.

The Honda BF150AK2 LCU outboard features BLAST™ ready-to-start technology that gets the engine up to velocity in seconds. The BLAST™ (Boosted Low Speed Torque) delivers high torque even at low speeds by unleashing powerful thrust from startup. The ECU automatically advances the ignition timing, and at the same time increases the fuel/air ratio to give you more thrust from low speeds.

Honda BF150AK2 LCU is equipped with ECOmo's special poor-blend combustion control system ensures remarkable fuel economy right from revs and performance. The Honda BF150AK2 LCU models are NMEA2000® compliant.

HONDA BF150AK2 LCU TECHNICAL FEATURES



Net Power (kW): 110.3  
Net Power (Hp): 150  
Displacement: 2354 cm<sup>3</sup>  
Shaft length: Long  
Dry weight (Kg): 217  
Starter: Electric  
Ignition system: Electronic PGM-IG  
Type of control Remote  
Setup and engine lifting: Electric  
Transom height (mm): 508  
Length (mm): 845  
Width (mm): 580  
Height (mm): 1665  
Bore x stroke: 87 x 99 mm  
Engine Brand: Honda  
Engine Type: DOHC, 4 stroke  
Number of cylinders: 4  
Speed at full throttle (rpm): 5000-6000  
Cooling system: Water  
Battery charging capacity (A): 40  
Exhaust system: Propeller hub  
Propeller rotation: Counter-rotating

Are you looking for an outboard with different technical specifications? Here you can find the full range of Honda or other specialized brands.

The images are purely indicative.

#### **Product features:**

Fuel: Gasoline  
Engine: DOHC, 4 tempi  
Ignition: Electronic PGM-IG  
Starting system: Electric  
Engine capacity (cm<sup>3</sup>): 2354  
Number cylinders: 4  
Cylinders' position: In line  
Cooling: Water (with thermostat)  
Bore x stroke (mm): 87 x 99  
Reduction ratio: 2.14  
Rpm at full throttle (rpm): 5000 - 6000  
Appearance and engine lifting: Electric  
Transom height (mm): 508

---

Net power (kW): 110.3  
Length (mm): 845  
Width (mm): 580  
Height (mm): 1665  
Dry weight (Kg): 217  
Shaft Length: L  
Controls: Remote