



# CGM PR4-160LSP

## Product description:

CGM PR4-160LSP LED Light Tower with CGM petrol engine

The CGM PR4-160LSP is a simple light tower with manual lifting winch equipped with 4 floodlights capable of delivering a light output of 160W each.

CGM PR4-160LSP consists of a trolley with lockable handles with safety grip.

CGM PR4-160LSP includes CGM 6000SP SUPER POWER gasoline engine with electric start, 3000 rpm and air cooling.

CGM PR4-160LSP is equipped with a galvanized steel lifting tower capable of extending to a maximum height of 5.5 meters, including 3 feet of stabilization to secure the light tower once opened.

## CGM PR4-160LSP TECHNICAL SPECIFICATIONS

Lights: 4 160W LEDs

Lit Area: 2200 Sq Ft

Max Height: 5.5 Mt

Lift: Manual

Telescopic Pole: galvanized steel

Wind stability: nr 3 stabilizers

Lumen per light: 20350 lm

Electrical power: 6 KVA / 5,4 KW

Rotation: 355 degrees

Trolley: Slow

Drives for forklift: nr 2

Power socket: 16A 230V

Voltage: 230V



Frequency: 50 Hz  
Number of turns: 3000 turns/mn  
Engine: 6000SP SUPER POWER CGM  
Fueling: Gasoline  
Type of starting: Electric  
Tank capacity: 25 Lt  
Autonomy with working lights: 20 hr  
Engine power: 14 Hp  
N. Cylinders: 1  
Intake: Aspirated  
Cooling: Air  
Width: 1300 mm  
Length: 900 mm  
Height Closed: 2160 mm  
Height Open: 5500 mm  
Dry Weight: 280 Kg  
Firing: Air  
AVR

You can find many other different light towers in the section dedicated to lighting systems.

Images are purely indicative

**Product features:**

Phase: Single phase  
Continuous power single phase (KW): 5.4  
Continuous power single phase (KVA): 6  
Fuel: Gasoline  
Frequency (Hz): 50  
Voltage (V): 230  
Sockets configuration: 1 x 230V 16A  
Engine: 6000SP SUPER POWER CGM  
Engine rpm (rpm): 3000  
Starting system: Electric  
Engine capacity (cm<sup>3</sup>): 420  
Number cylinders: 1  
Cooling: Air  
Alternator: CGM  
Poles: 2  
Type of lamps: LED

---

Lamps: 4 x 160 W  
Telescopic pole: Galvanized steel  
Illuminated area (m<sup>2</sup>): 2200  
Total lumens (Lm): 81400  
Lifting System: Manual lifting system  
Maximum height (m): 5.5  
Mast rotation: 355°  
Open size (mm): 1300 x 900 x 5500  
Closed size (mm): 1300 x 900 x 2160  
Transportability: Slow Trailer  
Fuel tank capacity (L): 25  
Running time (h): 20  
Acoustic pressure: 70 dB(A) at 7 m  
Dry weight (Kg): 280  
Silenced: Yes  
Engine manufacturer: CGM