



CGM FXS4-320L TOWERGEN

Product description:

CGM FXS4-320L TOWERGEN 4 X 320W

CGM FXS4-320L TOWERGEN is a light tower with diesel generator and manual lifting winch equipped with 4 floodlights able to deliver a light power of 320W each.

CGM FXS4-320L TOWERGEN is equipped with a KOHLER KD350 3000 rpm diesel engine with liquid cooling capable of delivering a mechanical power of 5.8 Hp.

CGM FXS4-320L TOWERGEN is equipped with a galvanized steel lifting tower capable of extending up to a maximum height of 7.5 meters, including 4 stabilization feet to secure the light tower once opened.

CGM FXS4-320L is equipped with LINZ ELECTRIC alternator which increases the efficiency of the KOHLER engine thanks to its integrated AVR, allowing high efficiency with reduced consumption. The light tower has a 40 Lt capacity tank, which allows the continuous operation of the CGM for 84 hours.

TECHNICAL FEATURES CGM FXS4-320L TOWERGEN

Floodlights: 4 LED 350W

Illuminated Area: 4500 Mq

Max Height: 7.5 Mt

Lift: Manual

Telescopic Pole: Galvanized steel with self-braking winch from 450

Wind stability: nr 4 stabilizers

Guides for forklift forks: n.4

Lumen per light: 41550 lm

Continuous electric power: 4.2 KVA

Rotation: 355 degrees

Towing trolley: Slow
Power outlet: 16A 230V
Voltage: 230V
Frequency: 50Hz
Number of revolutions: 3000 revolutions/mn
Engine: KOHLER KD350 Diesel
Starting type: Electric battery
Tank capacity: 40 Lt
Autonomy with working lights: 84 hr
Engine power: 5.8 Hp / 4.3 KW
N. Cylinders: 1
Suction: Aspirated
Cooling: Air
Alternator: LINZ ELECTRIC
Type: Brushless
No. of Poles: 2
Width: 1200 mm
Length Closed: 1550 mm
Length Opened: 2400 mm
Height Closed: 2700 mm
Height Opened: 7500 mm
Dry weight: 625 Kg
Voltage regulation: AVR

Looking for a light tower with different features? Here you can find the full range CGM or other specialized brands.

Images and technical data are not binding and may be subject to revision by the supplier.

Product features:

Phase: Single phase
Continuous power single phase (KVA): 4.2
Fuel: Diesel
Frequency (Hz): 50
Voltage (V): 230
Sockets configuration: 1 x 230V 16A
Engine: KOHLER KD350
Engine rpm (rpm): 3000
Starting system: Electric
Number cylinders: 1
Cooling: Air
Alternator: Linz

Poles: 2
Tank capacity (L): 40
Type of lamps: LED
Lamps: 4 x 320 W
Telescopic pole: Galvanized steel
Illuminated area (m²): 4500
Lifting System: Manual lifting system
Maximum height (m): 7.5
Mast rotation: 355°
Open size (mm): 2400 x 1200 x 7500
Closed size (mm): 1550 x 1200 x 2700
Dry weight (Kg): 625
AVR: Yes