



MECC ALTE ECP28-2L/2 C-TYPE THREE-PHASE ALTERNATOR 30KVA

Product description:

MECC ALTE ECP28-2L/2 C-TYPE ALTERNATOR 30KVA THREEPHASE

Alternator MECC ALTE ECP28-2L/2 C-TYPE with a power of 30KVA, this unit has a Brushless self-exciting and self-regulating operation equipped with voltage regulator **DSR**.

The ECP28-2L/2 C-TYPE alternator is designed to operate at 50 or 60 HZ frequency, the possibility of working on these two frequencies makes it possible to apply it for any service voltage increasing its versatility, for the correct operation.

The ECP28-2L/2 alternators mount button-type diodes, mounted directly in the exciter's diode holder, or mounted on a detachable diode bridge, divided into three sectors. In the case of the bridge, each individual diode can be verified very easily with a multimeter specially set for diode verification.

MECC ALTE ECP28-2L/2 C-TYPE is supplied with 12 terminals (7 clamps), with which it is normally possible to connect the alternator both star series and star parallel. According to the needs it is possible to pass from a connection to another one keeping in mind that it is necessary to verify the DSR connection.

ECP28-2L/2 C-TYPE can be used as singlephase depending on the needs. MECC ALTE ECP28-2L/2 is equipped with digital current regulator DSR . The regulator is suitable for operation on both threephase and singlephase generators, allowing fast, accurate and reliable set-up.

All MECC ALTE ECP28 alternators have the MAUX auxiliary winding to power the DSR digital regulator. You can connect the DSR voltage regulator to your PC via the DxR2 USB interface and DxR TERMINAL software to query/download alarms and settings for analysis.

Select the alternator that reflects the **technical specifications you require**, visit our dedicated section to find out how.

TECHNICAL FEATURES OF 22KVA MECC ALTERNATOR ECP28-2L/2 C-TYPE

Phase Type: Singlephase / ThreePhase
Maximum ThreePhase Power: 28. 8KW
Threephase continuous power: 24KW
Threephase maximum power: 36KVA
Threephase continuous power: 30KVA
Frequency: 50 / 60 Hz
Voltage: 230 / 400 V
Protection class: IP23
Alternator speed: 3000 rpm
Number of poles: 2
Efficiency: 87. 2%
Weight: 141 kg
Width: 466.7 mm
Length: 548.8 mm
Height: 460 mm
Constant speed alternator
Brushless
Voltage regulator: AVR

Looking for a product with different features? Here you can find the full range MECC ALTE and other specialized brands.

Images and technical data are not binding and subject to changes by the manufacturer

Product features:

Phase: Single phase / Three phase
Maximum power single phase (KW): 20 (50Hz) - 24 (60Hz)
Continuous power single phase (KW): 18.9 (50Hz) - 22.7 (60Hz)
Maximum power single phase (KVA): 20 (50Hz) - 24 (60Hz)
Continuous power single phase (KVA): 18.9 (50Hz) - 22.7 (60Hz)
Maximum power three phase (KW): 25.2 (50Hz) - 30.4 (60Hz)
Continuous power three phase (KW): 24 (50Hz) - 28.8 (60Hz)
Maximum power three phase (KVA): 31.5 (50Hz) - 38 (60Hz)
Continuous power three phase (KVA): 30 (50Hz) - 36 (60Hz)
Frequency (Hz): 50 / 60
Voltage (V): 230 / 400
Engine rpm (rpm): 3000
Poles: 2
Single-phase power (KVA): 24
Three-phase power (KVA): 38

Efficiency (%): 87.2

Protection degree: IP23

Acoustic pressure: 74 dB(A) at 7 m

Length (mm): 466

Width (mm): 548.8

Height (mm): 460

Brushes: No

PMG: No

Type of alternator: Constant Speed

Voltage regulator: AVR

Weight (Kg): 141