



# MECC ALTE ECP32-L/2 C-TYPE THREE PHASE ALTERNATOR 82 KVA AVR

## Product description:

MECC ALTE ECP32-M/2 C-TYPE THREEPHASE ALTERNATOR 66 KVA DSR

Alternator MECC ALTE ECP32-M/2 C-TYPE threephase with a power of 66KVA, this unit has a Brushless self-exciting and self-regulating operation equipped with **DSR** voltage regulator.

The alternator ECP32-L/2 is complete with self-regulation which is achieved by means of a digital electronic regulator powered by an auxiliary winding.

The MECC ALTE ECP32-L/2 alternator is ruggedly designed to meet industry requirements and the most demanding technological specifications needed in various applications. They are available as a bearing in single or double bearing configuration.

The ECP32-L/2 alternator consists of a fixed stator with inclined slots and a rotating inductor. In addition, models above 15 KVA are equipped with a damping cage as standard.

The high-quality two-component insulating resin used by Mecc Alte ECP32-L/2, is a polyester specially developed for use in vacuum or dip and drip impregnation machines. It has superior adhesion strength characteristics, high chemical and moisture resistance, and is suitable for uses up to 212°C.

MECC ALTE ECP32-L/2 alternators comply with Italian CEI 2-3 file 11111. This corresponds to the European standard EN 60034-1 and the international standard IEC 60034-1, is linked to the British standard BS 4999 Part 101, is equivalent to the German standard VDE 0530 Part 1 and is included in the French standard NF 51.111.

TECHNICAL CHARACTERISTICS MECC ALTE ALTERNATOR ECP32-M/2 C-TYPE

Phase Type:SinglePhase / ThreePhase

Maximum SinglePhase Output:  
(50Hz) 54KVA / 54KW  
(60Hz) 65KVA / 65KW  
Continuous SinglePhase Output:  
(50Hz) 48.8KVA / 48.8KW  
(60Hz) 58.5KVA / 58.5KW  
Maximum ThreePhase Output:  
(50Hz) 82KVA / 65.6KW  
(60Hz) 98.5KVA / 78. 8KW  
Continuous threephase output:  
(50Hz) 75KVA / 60KW  
(60Hz) 90KVA / 72KW  
Frequency: 50 / 60 Hz  
Voltage: 230 / 400 V  
Degree of protection: IP23  
Alternator turns: 3000 rpm  
Number of poles: 2  
Efficiency: 89%  
Width: 553mm  
Length: 743. 5mm  
Height: 542.7 mm  
Weight: 231 Kg  
Constant speed alternator  
Brushless  
Voltage regulator: AVR

Looking for a product with different features? Here you can find the full range MECC ALTE and other specialized brands.

Images and technical data are not binding and subject to changes by the manufacturer

**Product features:**

Phase: Single phase / Three phase  
Maximum power single phase (KW): 54 (50Hz) - 65 (60Hz)  
Continuous power single phase (KW): 48.8 (50Hz) - 58.5 (60Hz)  
Maximum power single phase (KVA): 54 (50Hz) - 65 (60Hz)  
Continuous power single phase (KVA): 48.8 (50Hz) - 58.5 (60Hz)  
Maximum power three phase (KW): 65.6 (50Hz) - 78.8 (60Hz)  
Continuous power three phase (KW): 60 (50Hz) - 72 (60Hz)  
Maximum power three phase (KVA): 82 (50Hz) - 98.5 (60Hz)  
Continuous power three phase (KVA): 75 (50Hz) - 90 (60Hz)  
Frequency (Hz): 50 / 60

---

Voltage (V): 230 / 400  
Engine rpm (rpm): 3000  
Poles: 2  
Single-phase power (KVA): 65  
Three-phase power (KVA): 98.5  
Efficiency (%): 89  
Protection degree: IP23  
Acoustic pressure: 77 dB(A) at 7 m  
Length (mm): 553  
Width (mm): 743.5  
Height (mm): 542.7  
Dry weight (Kg): 231  
Brushes: No  
PMG: No  
Type of alternator: Constant Speed  
Voltage regulator: AVR  
Weight (Kg): 225