

# GREENPOWER GP30 TR-C PTO GROUP 27KVA



Product price:

**2.075,75 € tax excluded**

## Product description:

GREENPOWER GP30 TR/S-C PTO DRIVE GENERATOR 27KVA

GREENPOWER GP30 TR/S-C is a cardan shaft generator complete with ZANARDI ATO28/4-1L alternator capable of delivering a power of 27KVA.

The GREENPOWER GP30 TR/S-C is very reliable as it has been built and designed using top quality materials. The PTO shaft generator is easy to transport, install and position due to the compact size, this model is ideal to be mounted on a tractor unit.

The GREENPOWER GP30 TR/S-C has a required tractor power of 60 HP and a PTO speed of 430 rpm.

These compact, rugged and easy-to-use generator sets come complete with a 3-point hitch base for secure attachment to any tractor.

The design and the realization of the generators takes place completely inside the company, peculiarities that allow GreenPower to customize the product and its delivery in extremely short times, also thanks to the presence in stock of more than 1000 engines and alternators.

The generator GREENPOWER GP30 TR/S-C is equipped with IP44 panel with CASA socket (63A 400V) and FIELD sockets (63A 400V - n.2 x 32A 400V - n.1 schuko), CASA-CAMPO selector, insulation control, min/max voltage and min/max frequency relay, digital multimeter.

## TECHNICAL FEATURES GREENPOWER GP30 TR/S-C

Phase type: Single/ Threephase

Threephase maximum power: 30 KVA / 24 KW

Threephase continuous power: 27 KVA / 21.6 KW

Singlephase continuous power: 20 KVA / 16 KW

Voltage: 400 - 230 V

Frequency: 50 Hz  
Engine speed: 3000 rpm  
Necessary tractor power: 60 hp  
PTO speed: 430 rpm / min  
Alternator: ZANARDI ATO28 / 4-1L  
Voltage regulator: Compound  
Length: 855 mm  
Width: 580 mm  
Height: 985 mm  
Weight: 163 Kg

Are you looking for a shaft generator with different technical characteristics? Here you can find the full range of GreenPower or other brands specializing in the field

Images and technical data are not binding and may be subject to revision by the manufacturer.

**Product features:**

Phase: Single phase / Three phase  
Continuous power single phase (KW): 16  
Continuous power single phase (KVA): 20  
Maximum power three phase (KW): 30  
Continuous power three phase (KW): 21.6  
Maximum power three phase (KVA): 24  
Continuous power three phase (KVA): 27  
Frequency (Hz): 50  
Voltage (V): 230 / 400  
Engine rpm (rpm): 1500  
Alternator: ZANARDI ATO28/4-1L  
Poles: 4  
Protection degree: IP23  
PTO speed (round/min): 440  
Required tractor power: 60 HP  
Length (mm): 855  
Width (mm): 580  
Height (mm): 985  
Dry weight (Kg): 163  
Silenced: No  
Super silenced: No  
Voltage regulator: Compound