

# GREEN POWER 88KVA



**Product price:**

**11.104,00 € tax excluded**

## Product description:

The 1500 rpm generators are designed for versatile use, from construction sites to industry, from agriculture to civil protection.

Robust welded steel frames with built-in tank of variable capacity, engines and alternators supplied by the most important manufacturers in the sector and cutting-edge control units are the elements to ensure generators of excellent quality.

The hoods are made of steel, which allows them to be used in tropical environments. The Green Power covers guarantee maximum accessibility for maintenance and cleaning operations.

THE strong point is the design and implementation within the company, a feature that helps to reduce the time to market of the product and allows any customization.

The image is purely indicative.

## Product features:

Phase: Three phase

Maximum power three phase (KW): 70

Continuous power three phase (KW): 64

Maximum power three phase (KVA): 88

Continuous power three phase (KVA): 80

Fuel: Diesel

Frequency (Hz): 50

Voltage (V): 230 / 400

Engine: PERKINS 1104A-44TG2, 4 stroke turbo-aftercooler

Engine rpm (rpm): 1500

Speed governor: Mechanical

Starting system: Electric

Engine capacity (cm<sup>3</sup>): 4400

---

Number cylinders: 4  
Cylinders' position: In line  
Cooling: Water  
Alternator: Linz PRO22SC/4, synchronous, brushless  
Poles: 4  
Fuel tank capacity (L): 100  
Consumption (L/h): 14 at 75% of the load  
Running time (h): 9.62 h al 75% del carico  
Length (mm): 2100  
Width (mm): 1000  
Height (mm): 1400  
Dry weight (Kg): 1315  
Silenced: Yes  
Super silenced: Yes  
ATS Switch device : Optional  
Voltage regulator: AVR