



# AURORA TOWER LIGHT DELTA L 6X160

## Product description:

AURORA TORRE FARO DELTA L6X160

AURORA DELTA L6X160 is a lighting tower with hydraulic lifting equipped with 6 floodlights capable of delivering a light output of 160W each.

AURORA DELTA L6X160 is equipped with a galvanized steel lifting tower able to extend up to 8,5 meters of maximum height, including 4 stabilization feet to secure the light tower once opened.

AURORA DELTA L6X160 can be connected in series to other 6 modules allowing you to have a properly illuminated working area for any kind of work you have to do.

The lenses of the AURORA light tower are equipped with an extremely special optic designed specifically for the civil engineering and construction sectors. This innovative, fully directional LED lens design ensures maximized light output and reduced waste.

The safety stop stops the descent at a safe height that avoids the risk of collisions with headlamps during normal descent or in case of sudden breakage of the telescopic cables or the automatic brake of the lifting winch.

AURORA DELTA L6X160 is characterized by extremely compact dimensions and a squared shape that optimize and facilitate its positioning and transport on mobile vehicles. The base, with 4 adjustable and removable anti-tip stabilizers, guarantees a wind stability of 110 Km/h.

## TECHNICAL CHARACTERISTICS AURORA DELTA L6X160

Manufacturer: Green Power

Projectors: 6 160W LEDs

Lit Area: 4200 Square meters



Total Lumens: 122100 lm  
Max Height: 8.5 Mt  
Lift: Hydraulic  
Extra sockets: 1 x 16A CEE / 230 V  
Pole sections: 6  
Manual stabilizers: 4  
Lifting hooks: 4  
Max wind resistance: 110 Km/h  
Fork passage guides: STD  
Transportation: Stationary  
Voltage: 230V  
Frequency: 50 Hz  
Contained tower dimensions: 980x1180x2237 mm  
Open tower dimensions: 2450x2658x8500 mm  
Dry weight: 550 Kg

Looking for a product with different characteristics? Here you can find the full range Green Power or other specialized brands.

The images and technical data are not binding and may be subject to revision by the supplier.

**Product features:**

Frequency (Hz): 50  
Voltage (V): 230  
Sockets configuration: 1 x 16A CEE / 230 V  
Starting system: Electric  
Type of lamps: LED  
Lamps: 6 x 160W  
Telescopic pole: Galvanized steel  
Illuminated area (m<sup>2</sup>): 4200  
Total lumens (Lm): 122100  
Lifting System: Hydraulic lifting system  
Maximum height (m): 8.5  
Mast rotation: 350°  
Open size (mm): 2450x2658x8500  
Closed size (mm): 980x1180x2237  
With generator / Without generator: Without generator  
Transportability: Stationary  
Dry weight (Kg): 550