



AURORA TOWER LIGHT DELTA L 4X320

Product price:

7.305,00 € tax excluded

Product description:

AURORA TORRE FARO DELTA L4X320

AURORA DELTA L4X320 is a light tower with hydraulic lifting equipped with 4 floodlights capable of delivering a light output of 320W each.

AURORA DELTA L4X320 is equipped with a galvanized steel lifting tower able to extend up to 8,5 meters of maximum height, including 4 stabilization feet to secure the light tower once opened.

The AURORA DELTA L4X320 light tower has an input plug and a 16A 230V output socket for the with which it can be combined with other units.

AURORA DELTA L4X320 is designed to be combined with a generator set and can be connected in series in order to use one generator for several lighting units.

The AURORA light tower lenses feature extremely special optics designed specifically for the civil engineering and construction industries. This innovative fully directional LED lens design ensures maximization of light diffusion and reduction of waste.

AURORA DELTA L4X320 is characterized by extremely compact dimensions and square shape that optimize and facilitate its positioning and transportation on mobile vehicles. The base, with 4 adjustable and removable anti-tip stabilizers, guarantees a wind stability of 110 Km/h.

TECHNICAL CHARACTERISTICS AURORA DELTA L4X320

Manufacturer: Green Power

Projectors: 4 LED 320W

Lit Area: 5000 square meters

Total Lumen: 166200 lm

Max Height: 8. 5 Mt



Lift: Hydraulic
Extra sockets: 1 x 16A CEE / 230 V
Pole sections: 6
Manual stabilizers: 4
Lifting hooks: 4
Max wind resistance: 110 Km/h
Fork passage guides: STD
Transportation: Stationary
Voltage: 230V
Frequency: 50 Hz
Contained tower dimensions: 980x1180x2237 mm
Open tower dimensions: 2450x2658x8500 mm
Dry weight: 550 Kg

Looking for a product with different characteristics? Here you can find the full range Green Power or other specialized brands.

Images and technical data are not binding and may be subject to revision by the supplier.

Product features:

Frequency (Hz): 50
Voltage (V): 230
Sockets configuration: 1 x 16A CEE / 230 V
Starting system: Electric
Type of lamps: LED
Lamps: 4 x 320W
Telescopic pole: Galvanized steel
Illuminated area (m²): 5000
Total lumens (Lm): 166200
Lifting System: Hydraulic lifting system
Maximum height (m): 8.5
Mast rotation: 350°
Open size (mm): 2450x2658x8500
Closed size (mm): 980x1180x2237
With generator / Without generator: Without generator
Transportability: Stationary
Dry weight (Kg): 550