



MASE EA 40 BS

Product price:

900,00 € tax excluded

Product description:

MASE EA 40 BS SINGLE-PHASE GENERATOR 4 KVA

MASE EA 40 BS is a single-phase generator equipped with a BRIGGS & STRATTON XR950 gasoline engine, capable of delivering a maximum power of 4 KVA.

The MASE EA 40 BS single-phase generator provides reliable power for home, business and recreational environments, safely powering home appliances and other electronic devices.

The generator is as easy to install and operate as it is to start and stop thanks to clear, intuitive controls. MASE EA 40 BS is equipped with a engine BRIGGS & STRATTON XR950 gasoline. These are very reliable engines that provide efficient combustion and **low fuel consumption.** The engines with which the generators are equipped also feature a protection system that causes the engine to stop if the oil level is too low.

MASE EA 40 GH thanks to the stage V emission standard, mobile use of the machine is possible, without having the need to secure it to the ground. This guarantees you an incredible versatility thanks also to the reduced weight and dimensions, MASE EA 40 GH will always be close to you in any use.

MASE EA 40 GH has an all-steel structure and a large metal tank. The generator guarantees an efficient and silent operation thanks to the BRIGGS & STRATTON XR950 engine, which allows to deliver a maximum power of 4 KVA.

TECHNICAL CHARACTERISTICS MASE EA 40 GH

Maximum power Single-phase: 4 KVA

Fuel: Gasoline Voltage: 230 V Frequency: 50 Hz





Motor: BRIGGS & STRATTON XR950

Cooling: Air

Starting: Manual

Protection class: IP 23

Length: 610 mm Width: 360 mm Height: 410 mm

Are you looking for a power generator with different characteristics? Here you can find the full range of products MASE or other brands specializing in the field

Images and technical data are not binding and may be subject to revision by supplier.

Product features:

Phase: Single phase

Maximum power single phase (KW): 3.85

Fuel: Gasoline

Frequency (Hz): 50 Voltage (V): 230

Sockets configuration: 2 x 230V SCHUKO

Engine rpm (rpm): 3000 Starting system: Manual Engine capacity (cm³): 196

Number cylinders: 1

Cooling: Air

Alternator: Synchronous Fuel tank capacity (L): 3.1

Consumption (L/h): 1.5 al 75% del carico

Acoustic power: 98 dB(A)

Acoustic pressure: 73 dB(A) at 7 m

Length (mm): 610 Width (mm): 360 Height (mm): 410 Dry weight (Kg): 38

Silenced: No

Super silenced: No ATS Switch device: No Voltage regulator: No

Engine manufacturer: Honda

