



VETUS GLX20TI THREE PHASE MARINE GENERATOR 20KVA



Product price:

14.280,00 € tax excluded

Product description:

VETUS GLX14TI MARINE GENERATOR 14KVA

VETUS GLX20TI is a 20KVA three-phase boat generator, with a 1500 rpm diesel-powered, water-cooled VH4.65 engine and digital control panel.

VETUS GLX20TI operates at a fixed number of engine revolutions, and can be placed even in small spaces thanks to their compact size. The high quality design, insulation and materials of the generators in this range ensure reliability and durability.

All VETUS GLX20TIs come with the handy digital control panel, with which the user can automatically start or shut down the generator.

The alternator of the VETUS GLX20TI marine generator is brushless, with AVR voltage regulator, class H insulation and IP 44 protection of internal parts. The AVR voltage regulator avoids voltage surges and does not allow to burn sensitive electronic devices such as pc, smartphone or appliances in general.

The VETUS GLX20TI thanks to its AVR voltage regulator is a robust worker. Thanks to the pure sine wave, this generator is suitable for use in combination with electronic components such as a computer. In other words, a compact and reliable companion for your boat.

The VETUS GLX20TI thanks to its small size and its modest weight is suitable to be installed on any type of boat whether for work or recreational use.

TECHNICAL CHARACTERISTICS VETUS GLX20TI

Phase type: Three-phase

Maximum three-phase power (KW): 16

Maximum three-phase power (KVA): 20



Fuel: Diesel
Voltage: 230 V / 400 V
Frequency: 50 Hz
Engine: VH4.65
Cooling: Water
Engine RPM: 1500 rpm
Starting: Automatic
Acoustic power: 57 dB (A)
Protection class: IP 55
Length: 1292 mm
Width: 739mm
Height: 694mm
Weight: 505 Kg

Are you looking for a generator for boats with different technical characteristics? Here you can find the whole range of VETUS or other brands specializing in this field.

Images and technical data are not binding and may be subject to revision by the supplier.

Product features:

Phase: Three phase
Maximum power three phase (KW): 16
Maximum power three phase (KVA): 20
Fuel: Diesel
Frequency (Hz): 50
Voltage (V): 230 / 400
Engine: VH4.65
Emissions Regulations: Non Emissionati
Engine rpm (rpm): 1500
Starting system: Electric
Cooling: Water
Alternator: Synchronous, brushless
Acoustic power: 57 dB (A)
Length (mm): 1292
Width (mm): 739
Height (mm): 694
Dry weight (Kg): 505
Product type: Generator
Voltage regulator: AVR

