

ULTIMATE75-S600+FIXED UNDERWATER LED SPOTLIGHT FLUSH



Product price:

1.591,00 € tax excluded

Product description:

ULTIMATE75-S600+FIXED UNDERWATER LED spotlight

ULTIMATE75-S600+FIXED is an underwater Led spotlight for boats capable of generating a light output of 150W in Alliminium and borosilicate glass.

ULTIMATE75-S600 is a submersible spotlight for welding in steel or aluminum hulls. The ULTIMATE75-S600 gives the possibility to make maintenance and upgrades without the need to bring the boat dry, this will give you the possibility to make a constant maintenance increasing the life of the spotlight.

ULTIMATE75 is recommended for boats over 30m, installing each fixture 1.5-5m apart for the best illumination.

The ULTIMATE75-S600 underwater spotlight can be supplied in three different designs:

- ULTIMATE75-S600+FIXED for a flush installation angle
- ULTIMATE75-S630+FIXED for an installation angle of 30°.
- ULTIMATE75-S650+FIXED for an installation angle of 50°.

TECHNICAL CHARACTERISTICS ULTIMATE75-S600+FIXED

Hull Material: Stainless steel and aluminum

Boat size: Up to 30 m

Transom Spacing: 1.5-2.0 m

P & S Spacing: 1.5-5 m

Beam Angle: 65° / 77° / 100°

Maximum Power: 150 W

Lumens: 12000

Typical LED life expectancy: 3000 h



Minimum and maximum working voltage: 110-240V AC

Current / Amplifier: 1.4 - 0.7 A

Driver Type: External

Output Driver: N/A

Output Control: On / Off

Device Length: 250 - 306 mm

Device Diameter: 120 - 140 mm

Device Profile: N/A

Required removal space: 170 mm

Total Weight: 5 - 6.3 Kg

Cut Hole: N/A

Material: Alluminium

Growth resistant lens: Borosilicate glass

Looking for an Underwater spotlight with different features? Here you can find the section dedicated to nautical lighting systems with brands specializing in the field.

Images and technical data are not binding and may be subject to revisions by the manufacturer.

Product features:

Voltage (V): 110-240

Diameter (Ø): 120 - 140 mm

Power (W): 150

Average life of LEDs (hrs): 3000

Type of lamps: LED

Length (mm): 250 - 306

Weight (Kg): 5 - 6.3

Video: mSzY-vFJivE

