

# NANNI QMS25M MARINE GENERATOR 25KVA



## Product description:

### NANNI QMS25M MARINE GENERATOR 25KVA

NANNI QMS25M is a single-phase marine generator equipped with a Kubota 4-stroke diesel engine capable of delivering a maximum power of 25KVA.

The NANNI QMS25M generator is equipped with a fast heating injector and glow plug and are positioned in the combustion chamber, ensuring engine start-up even at low temperatures.

The cooling system allows the NANNI QMS25M to operate at an optimal temperature. In the case of closed loop heat exchanger cooling, the coolant is cooled by seawater passing through the heat exchanger. The Super Glow system comes as standard equipment for cold weather starting.

The E-TVCS injection system produces an ideal mixture of air and fuel by creating three swirls in the combustion chamber. The combustion efficiency of the NANNI QMS25M is improved, resulting in low fuel consumption.

NANNI QMS25M is complete with freshwater and saltwater exchanger. Also available with a keel cooling system, also known as Keel Cooling.

The NANNI QMS25M's alternator provides 20KW of power in continuous operation and can produce up to 23KW. Protection level IP23 (protection level available on request).

## TECHNICAL FEATURES NANNI QMS25M

Maximum output: 23 KW

Continuous use output: 20 KW

Maximum output: 27.5 KVA

Continuous use output: 25 KVA

Fuel: Diesel

Voltage: 230 V  
Frequency: 50 Hz  
Engine: Kubota, 4 strokes  
Starting: Electric  
Insulation class: H  
Protection class: IP23  
Consumption: 8.2 Lt/h at full load  
Length: 1590 mm  
Width: 750 mm  
Height: 900 mm  
Weight: 550 Kg

Are you looking for a marine power generator with different technical features? Here you can find the full range NANNI or other brands specializing in the field.

The image and technical data are not binding and may be subject to revisions by the manufacturer.

#### **Product features:**

Phase: Single phase  
Maximum power single phase (KW): 23  
Continuous power single phase (KW): 20  
Maximum power single phase (KVA): 27.5  
Continuous power single phase (KVA): 25  
Fuel: Diesel  
Frequency (Hz): 50  
Voltage (V): 230  
Engine: Kubota, 4 stroke  
Engine rpm (rpm): 1500  
Starting system: Electric  
Number cylinders: 4  
Cylinders' position: In line  
Cooling: Water  
Inyección : Indirect (E-TVCS)  
Alternator: Electronic regulator  
Consumption (L/h): 8.2 at 100% of the load  
Length (mm): 1590  
Width (mm): 750  
Height (mm): 900

Dry weight (Kg): 550