

NANNI QMS21T MARINE GENERATOR 21KVA



Product description:

NANNI QMS21T MARINE GENERATOR 21KVA

NANNI QMS21T is a three-phase marine generator equipped with a Kubota 4-stroke engine with Diesel power supply capable of delivering a maximum power of 21KVA.

The cooling system allows the NANNI QMS21T to operate at an optimal temperature. In the case of closed-circuit heat exchanger cooling, the coolant is cooled by seawater passing through the heat exchanger.

The Kubota 4-stroke diesel engine is tested in all marine or industrial applications around the world, this engine ensures excellent performance and incredible reliability. The engine consists of cast iron tunnel type block and timing gear. The Super Glow system comes as standard equipment for cold weather starting.

The E-TVCS injection system produces an ideal mixture of air and fuel by creating three swirls in the combustion chamber. The combustion efficiency of the NANNI QMS21T is improved, resulting in low fuel consumption.

NANNI QMS21T comes complete with freshwater and saltwater exchanger. Also available with a keel cooling system, also known as Keel Cooling.

The alternators used in the QMS range are manufactured by Mecc Alte, a world leader in the production of compact synchronous alternators. All NANNI QMS generators feature an acoustic enclosure consisting of painted marine aluminum insulated panels, with multiple access doors for all necessary connections and maintenance items, including visual lifting access.

NANNI QMS21T TECHNICAL SPECIFICATIONS

Phase Type: Three Phase
Maximum Power: 16.7 KW
Continuous Power: 14.3 KW
Maximum Power: 21 KVA
Continuous Power: 18 KVA
Fuel: Diesel
Voltage: 400 V
Frequency: 50 Hz
Motor: Kubota, 4-stroke
Boosting: Electric
Isolation Class: H
Protection Class: IP23
Consumption: 4.8 Lt/h at full load
Length: 1130 mm
Width: 600 mm
Height: 700 mm
Weight: 378 kg

Are you looking for a marine power generator with different technical features? Here you can find the full range NANNI or other brands specializing in the field.

The image and technical data are not binding and may be subject to revisions by the manufacturer.

Product features:

Phase: Three phase
Maximum power three phase (KW): 16.7
Continuous power three phase (KW): 14.3
Maximum power three phase (KVA): 21
Continuous power three phase (KVA): 18
Fuel: Diesel
Frequency (Hz): 50
Voltage (V): 400
Engine: Kubota, 4 stroke
Engine rpm (rpm): 1500
Starting system: Electric
Number cylinders: 4
Cylinders' position: In line
Cooling: Water
Inyección : Indirect (E-TVCS)
Alternator: Electronic regulator
Protection degree: IP23

Motor insulation class: H

Consumption (L/h): 4.8 at 100% of the load

Length (mm):

Width (mm): 600

Height (mm): 700

Dry weight (Kg): 378

Silenced: Yes