

NANNI QMS32T MARINE GENERATOR 32KVA



Product description:

NANNI QMS32T 32KVA MARINE GENERATOR

NANNI QMS32T is a three-phase marine generator equipped with a 4-stroke Kubota engine with Diesel power supply capable of delivering a maximum power of 32KVA.

The cooling system allows the NANNI QMS32T to operate at an optimal temperature. In the case of closed circuit heat exchanger cooling, the coolant is cooled by seawater passing through the heat exchanger. The NANNI QMS32T marine generator is equipped with the Super Glow system for starting in cold temperatures without the risk of sudden engine failure.

The E-TVCS injection system produces an ideal mixture of air and fuel by creating three swirls in the combustion chamber. The combustion efficiency of the NANNI QMS32T is improved, resulting in low fuel consumption.

NANNI QMS32T is complete with freshwater and saltwater exchanger. Also available with a keel cooling system, also known as Keel Cooling.

The alternators used in the QMS range are manufactured by Mecc Alte, a world leader in the production of compact synchronous alternators. All NANNI QMS generators feature an acoustic enclosure consisting of painted marine aluminum insulated panels, with multiple access doors for all necessary connections and maintenance items, including visual lifting access.

NANNI QMS32T TECHNICAL SPECIFICATIONS

Phase Type: Three Phase

Maximum Power: 25.5 KW

Continuous Power: 23.2 KW

Maximum Power: 32.0 KVA

Continuous Power: 29. 1 KVA

Fuel: Diesel

Voltage: 400 V

Frequency: 50 Hz

Engine: Kubota, 4-stroke

Start: Electric

Isolation Class: H

Protection Class: IP23

Consumption: 8. 2 Lt/h at full load

Length: 1590 mm

Width: 700 mm

Height: 900 mm

Weight: 550 kg

Are you looking for a marine power generator with different technical features? Here you can find the full range NANNI or other brands specializing in the field.

The image and technical data are not binding and may be subject to revisions by the manufacturer.

Product features:

Phase: Three phase

Maximum power three phase (KW): 25.5

Continuous power three phase (KW): 23.2

Maximum power three phase (KVA): 32.0

Continuous power three phase (KVA): 29.1

Fuel: Diesel

Frequency (Hz): 50

Voltage (V): 400

Engine: Kubota, 4 stroke

Engine rpm (rpm): 1500

Starting system: Electric

Number cylinders: 4

Cylinders' position: In line

Cooling: Water

Inyección : Indirect (E-TVCS)

Alternator: Electronic regulator

Protection degree: IP23

Motor insulation class: H

Consumption (L/h): 8.2 at 100% of the load

Length (mm): 1590

Width (mm): 700

Height (mm): 900
Dry weight (Kg): 550
Silenced: Yes