

MOSA GE SX-12054 KDT

Product price:

7.415,00 € tax excluded



Product description:

MOSA GE SX-12054 KDT 8,8 KW

MOSA GE SX-12054 KDT threephase 8,8 KW generator set with Kubota diesel engine. The MOSA GE SX-12054 KDT generator set is equipped with electric start. The alternator of the MOSA GE SX-12054 KDT generator set is synchronous, threephase, self-excited, self-regulated with class H insulation.

This MOSA is compact and convenient to maneuver and transport thanks to its compact size, its weight of 350 kg as well as the practical central hook for lifting.

The MOSA GE SX-12054 KDT generator set with 38-liter fuel tank has a fuel consumption of 2.6 liters/hour at 75% load for an autonomy of more than 14 hours.

Sockets:

1x 400V 16A 3P+N+T CEE

2x 230V 16A 2P+T Schuko

Technical specifications MOSA GE SX-12054 KDT:

Maximum power three-phase: 8.8 KW

Three-phase continuous use power: 8 KW

Maximum power three-phase: 11 KVA

Three phase continuous use power: 10 KVA

Single-phase continuous use power: 7 KW

Single-phase continuous use power: 7 KVA

Fuel: Diesel

Voltage: 230 V / 400 V

Frequency: 50 Hz

Engine: Kubota KDW702

Starting: Electric

Consumption: 2.6 Lt/h at 75% of the load

Length: 1568 mm
Width: 710 mm
Height: 1115 mm
Weight: 350 Kg
Supersilenced

MOSA GE SX-12054 KDT portable generator set - Kubota diesel engine electric start -
Threephase alternator

If you are looking for another product such as MOSA GE SX-12054 KDT generator set then you
can browse our catalog for more terrestrial generator sets.

Images and technical data are not binding.

Product features:

Phase: Single phase / Three phase
Continuous power single phase (KW): 7
Continuous power single phase (KVA): 7
Maximum power three phase (KW): 8.8
Continuous power three phase (KW): 8
Maximum power three phase (KVA): 11
Continuous power three phase (KVA): 10
Fuel: Diesel
Frequency (Hz): 50
Voltage (V): 230 / 400
Sockets configuration: 1 x 400V 16A 3P+N+T CEE IP67 - 2 x 230V 16A 2P+T SCHUKO IP68
Engine: Kohler KDW702
Emissions Regulations: Stage 5
Engine rpm (rpm): 3000
Speed governor: Mechanical
Starting system: Electric
Engine capacity (cm³): 686
Number cylinders: 2
Oil capacity (L): 1.6
Cooling: Water
Alternator: Synchronous self-excited, self-regulated
Bore x stroke (mm): 75 x 77.6
Fuel tank capacity (L): 38
Consumption (L/h): 2.6
Running time (h): 14.5
Acoustic power: 93 dB(A)

Acoustic pressure: 68 dB(A) at 7 m
Length (mm): 1568
Width (mm): 710
Height (mm): 1115
Dry weight (Kg): 350
Silenced: Yes
Super silenced: Yes
Product type: Generator
ATS Switch device : Optional
Voltage regulator: AVR
Engine manufacturer: Kubota