

# MOSA GE SX-18000 KDT

Product price:

**6.750,00 € tax excluded**



## Product description:

MOSA GE SX-18000 KDT 14,4 KW

MOSA GE SX-18000 KDT threephase 14,4 KW generator set with Kohler diesel engine. The MOSA GE SX-18000 KDT generator set is equipped with electric start. The alternator of the MOSA GE SX-18000 KDT generator set is synchronous, threephase, self-excited, self-regulated with class H insulation.

This MOSA is compact and convenient to maneuver and transport thanks to its compact size, its weight of 370 kg as well as the practical central hook for lifting.

The MOSA GE SX-18000 KDT generator set with 38-liter fuel tank has a fuel consumption of 3,7 liters/hour at 75% load for an autonomy of more than 10 hours.

## Sockets:

1x 400V 32A 3P+N+T CEE

1x 230V 32A 2P+T CEE

1x 230V 16A 2P+T CEE

## Technical specifications MOSA GE SX-18000 KDT:

Maximum power three-phase: 14.4 KW

Three-phase continuous use power: 13.2 KW

Maximum power three-phase: 18 KVA

Three phase continuous use power: 16.5 KVA

Single-phase continuous use power: 9 KW

Single-phase continuous use power: 9 KVA

Fuel: Diesel

Voltage: 230 V / 400 V

Frequency: 50 Hz

Engine: Kohler KDW1003

Starting: Electric



Consumption: 3.7 Lt/h at 75% of the load  
Length: 1784 mm  
Width: 710 mm  
Height: 1115 mm  
Weight: 370 Kg  
Supersilenced

MOSA GE SX-18000 KDT portable generator set - Kohler diesel engine electric start -  
Threephase alternator

If you are looking for another product such as MOSA GE SX-18000 KDT generator set then you  
can browse our catalog for more terrestrial generator sets.

Images and technical data are not binding.

#### **Product features:**

Phase: Single phase / Three phase  
Continuous power single phase (KW): 9  
Continuous power single phase (KVA): 9  
Maximum power three phase (KW): 14.4  
Continuous power three phase (KW): 13.2  
Maximum power three phase (KVA): 18  
Continuous power three phase (KVA): 16.5  
Fuel: Diesel  
Frequency (Hz): 50  
Voltage (V): 230 / 400  
Sockets configuration: 1 x 400V 32A 3P+N+T CEE IP67 - 1 x 230V 32A 2P+T IP67 - 1 x 230V  
16A 2P+T IP67  
Engine: Kohler KDW1003  
Emissions Regulations: Stage 5  
Engine rpm (rpm): 3000  
Speed governor: Mechanical  
Starting system: Electric  
Engine capacity (cm<sup>3</sup>): 1028  
Number cylinders: 3  
Oil capacity (L): 2.5  
Cooling: Water  
Alternator: Synchronous self-excited, self-regulated  
Bore x stroke (mm): 75 x 77.6  
Fuel tank capacity (L): 38  
Consumption (L/h): 3..7  
Running time (h): 10.5



---

Acoustic power: 93 dB(A)  
Acoustic pressure: 68 dB(A) at 7 m  
Length (mm): 1784  
Width (mm): 710  
Height (mm): 1115  
Dry weight (Kg): 370  
Silenced: Yes  
Super silenced: Yes  
Product type: Generator  
ATS Switch device : No  
Voltage regulator: AVR  
Engine manufacturer: Kohler