

MOSA GE SX-18000 KDT

Product price:

6.750,00 € tax excluded



Product description:

MOSA GE SX-18000 KDT 14,4 KW

MOSA GE SX-18000 KDT threephase 14,4 KW generator set with Kohler diesel engine. The MOSA GE SX-18000 KDT generator set is equipped with electric start. The alternator of the MOSA GE SX-18000 KDT generator set is synchronous, threephase, self-excited, self-regulated with class H insulation.

This MOSA is compact and convenient to maneuver and transport thanks to its compact size, its weight of 370 kg as well as the practical central hook for lifting.

The MOSA GE SX-18000 KDT generator set with 38-liter fuel tank has a fuel consumption of 3,7 liters/hour at 75% load for an autonomy of more than 10 hours.

Sockets:

1x 400V 32A 3P+N+T CEE

1x 230V 32A 2P+T CEE

1x 230V 16A 2P+T CEE

Technical specifications MOSA GE SX-18000 KDT:

Maximum power three-phase: 14.4 KW

Three-phase continuous use power: 13.2 KW

Maximum power three-phase: 18 KVA

Three phase continuous use power: 16.5 KVA

Single-phase continuous use power: 9 KW

Single-phase continuous use power: 9 KVA

Fuel: Diesel

Voltage: 230 V / 400 V

Frequency: 50 Hz

Engine: Kohler KDW1003

Starting: Electric



Consumption: 3.7 Lt/h at 75% of the load
Length: 1784 mm
Width: 710 mm
Height: 1115 mm
Weight: 370 Kg
Supersilenced

MOSA GE SX-18000 KDT portable generator set - Kohler diesel engine electric start -
Threephase alternator

If you are looking for another product such as MOSA GE SX-18000 KDT generator set then you
can browse our catalog for more terrestrial generator sets.

Images and technical data are not binding.

Product features:

Phase: Single phase / Three phase
Continuous power single phase (KW): 9
Continuous power single phase (KVA): 9
Maximum power three phase (KW): 14.4
Continuous power three phase (KW): 13.2
Maximum power three phase (KVA): 18
Continuous power three phase (KVA): 16.5
Fuel: Diesel
Frequency (Hz): 50
Voltage (V): 230 / 400
Sockets configuration: 1 x 400V 32A 3P+N+T CEE IP67 - 1 x 230V 32A 2P+T IP67 - 1 x 230V
16A 2P+T IP67
Engine: Kohler KDW1003
Emissions Regulations: Stage 5
Engine rpm (rpm): 3000
Speed governor: Mechanical
Starting system: Electric
Engine capacity (cm³): 1028
Number cylinders: 3
Oil capacity (L): 2.5
Cooling: Water
Alternator: Synchronous self-excited, self-regulated
Bore x stroke (mm): 75 x 77.6
Fuel tank capacity (L): 38
Consumption (L/h): 3..7
Running time (h): 10.5



Acoustic power: 93 dB(A)
Acoustic pressure: 68 dB(A) at 7 m
Length (mm): 1784
Width (mm): 710
Height (mm): 1115
Dry weight (Kg): 370
Silenced: Yes
Super silenced: Yes
Product type: Generator
ATS Switch device : No
Voltage regulator: AVR
Engine manufacturer: Kohler