



MASE IS 11.6 T MARINE GENERATOR THREE-PHASE 10KVA EPA



Product description:

MASE IS 11.6 T THREE-PHASE MARINE GENERATOR 11.5KVA EPA

MASE IS11,6T three-phase marine generator with Yanmar 3TNV80F engine with diesel power supply at 1800 rpm capable of delivering a power of 11.5KVA.

The MASE IS11,6T marine generator is designed with a soundproof cabin that makes it **supersilenced**. The MASE IS11,6T marine generator is built with a diesel-powered Yanmar engine and synchronous, self-excited alternator with air/water cooling. With its small size, it is also suitable on small boats.

The marine generator CBU control module has a new design, the latest technology, a large display and micro-buttons for quick navigation of menus, start and stop procedures; IP54 protection rating. Very compact, 86x124mm and equipped with 10mts shielded cable, the CBU module has multiple functions for complete monitoring of the MASE IS11.6T.

The soundproof cabin of the MASE IS11,6T consists of a supporting structure in aluminum profile that supports panels in marine aluminum painted type 5754 extremely lightweight and high resistance to external agents. The excellent accessibility to the internal compartment makes maintenance operations easier even with the generator set installed in narrow spaces.

The MASE IS11.6T marine generator has **EPA certification** valid only for the **U.S. market**

Technical Features:

Phase Type: Three Phase
Maximum Power: 11.5KVA
Fuel: Diesel
Voltage: 240 - 480 V
Frequency: 60 Hz





Engine: Yanmar 3TNV80F, 4 Stroke
Length: 837 mm
Width: 568 mm
Height: 688 mm
Weight: 295 Kg

If you are looking for another generator as the MASE IS11,6T then you can see the entire catalog of marine generators.

Images and technical data are not binding.

Product features:

Phase: Three phase
Maximum power three phase (KVA): 11.5
Fuel: Diesel
Frequency (Hz): 50
Voltage (V): 240 - 480 V
Engine: Yanmar 3TNV80F
Engine rpm (rpm): 1800
Speed governor: Centrifugal, mechanical
Engine capacity (cm³): 1267
Number cylinders: 3
Cooling: Air / water (Intercooler W/A)
Inyección : Direct
Alternator: Synchronous, self-excited
Poles: 4
Lubrication: Forced
Consumption (L/h): 3.1 at 100% of the load
Acoustic pressure: 51 dB(A) at 7 m
Length (mm): 837
Width (mm): 568
Height (mm): 688
Dry weight (Kg): 295
Inverter: No
AVR: Yes
Compound: No
Silenced: Yes
Super silenced: Yes
Product type: Generator
Voltage regulator: AVR
Engine manufacturer: Yanmar

