

# GENERAC DF POWER JET 30 DUST FIGHTER STAGE V



**Product price:**

**7.807,50 € tax excluded**

## **Product description:**

### GENERAC DF POWER JET 30 DUST FIGHTER STAGE V

GENERAC DF POWER JET 30 is a dust collection system with Yanmar L100N V6 Stage V engine with Diesel power supply and a maximum horizontal radius of 30 m.

GENERAC DF POWER JET 30 has the purpose to solve in the most efficient way the problem of the abatement of the volatile dusts in all the environments where it is necessary to contain the emission of dust in atmosphere.

Thanks to the nebulization system of water particles up to 170 micron the Dust Fighter GENERAC binds dust particles and ends up on the ground. In addition, the nebulization method allows you to completely cover the dust cloud, saving you significant amounts of water.

The advantages of the GENERAC DF POWER JET 30 are twofold, involving the primary aspect of safeguarding the health of the workers engaged in the work and of the users of the area, but also that of safeguarding the mechanical efficiency of the worksite vehicles, drastically reducing machine stoppages due to air filter cleaning and breakdowns of the transmission components.

## TECHNICAL FEATURES GENERAC DF POWER JET 30

Maximum horizontal radius (no wind): 30 m

Water connection: UNI 45 / STORZ / CAMLOCK

Inlet pressure: 6 bar

Water consumption: 44 / 50 l/min

Water inlet filter: 170 micron

Rotation angle: 90°

Inclination: 0° / 40°

Engine: Yanmar L100N V6

Emissions standard: Stage V

Power supply: Diesel  
Cylinders: 1  
Engine cooling: Air  
Engine RPM: 2900 / 3100 rpm  
Fuel tank: 5.4 l  
Run at 75% load: 3 h  
Sound pressure: 87 dB(A) @ 7m  
Width: 1605 mm  
Length: 990 mm  
Height: 1563 mm  
Dry weight: 210 Kg

Looking for a Dust Fighter with different technical features? Here you can find the whole range of Generac or other specialized brands.

The images and technical data are not binding.

**Product features:**

Fuel: Diesel  
Engine: Yanmar L100N  
Emissions Regulations: Stage 5  
Engine rpm (rpm): 2900 / 3100  
Number cylinders: 1  
Cooling: Air  
Throwing distance (m): 30  
Maximum output capacity (Lt/min): 44 / 50  
Pressure (bars): 6  
Fuel tank capacity (L): 5.4  
Running time (h): 3 at 75% of the load  
Acoustic pressure: 87 dB (A) @ 7m  
Length (mm): 1605  
Width (mm): 990  
Height (mm): 1563  
Dry weight (Kg): 210