



GREEN POWER GP 8000 XM-HM SINGLE PHASE GENERATOR 6.6KVA

Product price:

1.115,10 € tax excluded

Product description:

GENERATOR GREEN POWER GP8000 XM/HM 6.6 KVA

The generator GREEN POWER GP8000 XM/HM single-phase is equipped with a gasoline-supply HONDA GX390 StageV engine capable of delivering 6.6KVA at 3000 rpm.

The GREEN POWER GP8000 XM/HM generator alternator is the LINZ E1C10 MI model (or equivalent primary brand) and is synchronous, single-phase, with brushes and class H insulation. The GREENPOWER GP8000 XM/HM is equipped with manual recoil start with self winding.

One of the main features of the generator is the motor/alternator coupling in single bearing by means of cone, on electrowelded steel base with interposition of vibration dampers.

The GREENPOWER GP8000 XM/HM is compact and easy to maneuver and transport thanks to its compact size, its weight of 82 kg as well as the practical tubular handles.

The generator with 6.1-liter tank has a fuel consumption of 2.1 liters/hour at 75% load.

STAGE V EMISSION STANDARDS

The STAGE V standard defines guidelines and limits for engine gas emissions. The regulation is respected through the installation of special anti-particulate filters in the gensets, but an indispensable condition for the filter to function correctly is that the genset works at its design temperature.

The electric control panel of the generator is composed of:

- Output sockets: 1x 230V 32A CEE / 1x 230V 16A SCHUKO
- Thermal circuit breaker

TECHNICAL FEATURES GREEN POWER GP8000 XM/HM



Phase Type: Single Phase
Continuous Use Power: 6 KVA / 6 KW
Maximum Power: 6.6 KVA / 6.6 KW
Motor: HONDA GX390
Motor RPM: 3000 rpm
Emission Standard: StageV
Start: Manual recoil
Fuel: Gasoline
Voltage: 230 V
Frequency: 50 Hz
Socket panel: 1 x Schuko 16A 230V / 1 x CEE 32A 230V
Tank capacity: 6. 1 l
Autonomy at 75% of load: 2.9 h
Consumption at 75% of load: 2.1 Lt/h
Length: 780 mm
Width: 570 mm
Height: 680 mm
Dry weight: 82 Kg

Are you looking for a generator with different technical characteristics? [HERE](#) you can find the area dedicated to GREEN POWER generators or other specialized brands.

Images and technical data are not binding.

Product features:

Phase: Single phase
Maximum power single phase (KW): 6.6
Continuous power single phase (KW): 6
Maximum power single phase (KVA): 6.6
Continuous power single phase (KVA): 6
Fuel: Gasoline
Frequency (Hz): 50
Voltage (V): 230
Sockets configuration: 1 x 230V 32A CEE - 1 x 230V 16A SCHUKO
Engine: Honda GX390
Emissions Regulations: Stage 5
Engine rpm (rpm): 3000
Starting system: Manual
Engine capacity (cm³): 389
Number cylinders: 1
Cooling: Air
Alternator: Linz

Poles: 2

Fuel tank capacity (L): 6.1

Consumption (L/h): 2.1 at 75% of the load

Running time (h): 2.95 at 75% of the load

Length (mm): 780

Width (mm): 570

Height (mm): 680

Dry weight (Kg): 82

Silenced: No

Super silenced: No

Product type: Generator

ATS Switch device : No

Voltage regulator: Capacitor / AVR (optional)

Engine manufacturer: Honda