

GREEN POWER GP 22 TR-C SINGLE-PHASE / THREE-PHASE PTO GENERATOR 20KVA



Product price:

1.780,85 € tax excluded

Product description:

GREEN POWER GP 22 TR-C SINGLE-PHASE / THREE-PHASE PTO GENERATOR 20KVA

Generator GREEN POWER GP22 TR-C single / three-phase PTO complete with MECC ALTE BTP3-2L/2 alternator capable of delivering a power of 20KVA

The GREEN POWER GP22 TR-C generator is very reliable as it has been built and designed using top quality materials. The PTO generator is easy to transport, install and position due to the compact size, this model is ideal to be mounted on a tractor unit.

The PTO generator for a correct operation, needs to be connected to a tractor capable of delivering a mechanical output of at least 40 HP and a PTO speed of at least 430 rpm.

These compact, robust and easy-to-use generators come complete with a 3-point hitch base for secure attachment to any tractor. The GREEN POWER GP22 TR-C generator is equipped with IP44 panel with magneto-thermal switch socket, differential, 32A 230V socket, 16A 230V Schuko socket and E31 digital module complete with: voltmeter, frequency meter and counter.

TECHNICAL FEATURES PTO GENERATOR GREEN POWER GP22 TR-C

Phase type: Singlephase / Threephase

Threephase maximum power: 22 KVA / 17.6 KW

Threephase continuous power: 20 KVA / 16 KW

Voltage: 230 - 400 V

Frequency: 50 Hz

Engine rpm: 3000 rpm

Necessary tractor power: 40 hp

PTO speed: 430 rpm



Alternator: MECC ALTE BTP3- 2L / 2 (OR QUIVALENT)

N ° of poles: 2

Insulation class: H

Protection class: IP 23

Voltage regulator: Compound

Length : 805 mm

Width: 580 mm

Height: 915 mm

Weight: 139 Kg

Are you looking for a PTO generator with different technical features? Here you can find the full range of Green Power or other brands specializing in the field

Images and technical data are not binding and may be subject to revisions by the manufacturer.

Product features:

Phase: Single phase / Three phase

Maximum power three phase (KW): 17.6

Continuous power three phase (KW): 16

Maximum power three phase (KVA): 22

Continuous power three phase (KVA): 20

Frequency (Hz): 50

Voltage (V): 230 / 400

Engine rpm (rpm): 3000

Alternator: MECC ALTE T20F-200/A

Poles: 2

Protection degree: IP23

PTO speed (round/min): 440

Required tractor power: 40 Hp

Length (mm): 805

Width (mm): 580

Height (mm): 915

Dry weight (Kg): 139

Silenced: No

Super silenced: No

Voltage regulator: Compound

