



# GREEN POWER GP77 TR/S SINGLE-PHASE / THREE-PHASE PTO GENERATOR 75KVA

Product price:

**3.972,00 € tax excluded**

## Product description:

GREEN POWER GP77 TR/S SINGLE-PHASE / THREE-PHASE PTO GENERATOR 75KVA

Generator GREEN POWER GP77 TR/S Three-phase PTO, equipped with MECC ALTE ECP32-3L/4 alternator capable of delivering a power of 75KVA, complete with **AVR voltage regulator**.

The GREEN POWER GP77 TR/S generator is very reliable as it has been built and designed using top quality materials. The generator is easy to transport, install and position due to its compact size, this model is ideal to be mounted on a tractor unit.

The PTO generator for a correct operation, needs to be connected to a tractor capable of delivering a mechanical output of at least 150 HP and a PTO speed of at least 420 rpm. The minimum parameters indicated are necessary for the correct functioning of the PTO generator, if they are not respected it is possible to cause malfunctions of the equipment.

The GREEN POWER GP66 TR/S generator is equipped with an electric panel complete with:

- Thermomagnetic circuit breaker
- Differential
- Socket 63 A 400 V
- Socket 16 A 230 V
- E31 digital module complete with: Voltmeter, Frequency meter and Hour meter

TECHNICAL FEATURES PTO GENERATOR GREEN POWER GP77 TR/S

Phase type: Single-phase / Three-phase

Maximum three-phase power: 78 KVA / 62.4 KW



---

Continuous three-phase power: 75 KVA / 60 KW  
Voltage: 230 - 400 V  
Frequency: 50 Hz  
Engine rpm: 1500 rpm  
Necessary tractor power: 150 hp  
PTO speed: 420 rpm  
Alternator: MECC ALTE ECP32- 3L / 4 (OR QUIVALENT)  
N ° of poles: 4  
Insulation class: H  
Protection class: IP 23  
Voltage regulator: AVR  
Length : 1140 mm  
Width: 750 mm  
Height: 1065 mm  
Weight: 454 Kg

Are you looking for a PTO generator with different technical characteristics? Here you can find the full range of Green Power or other brands specializing in the field

Images and technical data are not binding and may be subject to revisions by the manufacturer.

**Product features:**

Phase: Single phase / Three phase  
Maximum power three phase (KW): 78  
Continuous power three phase (KW): 60  
Maximum power three phase (KVA): 62.4  
Continuous power three phase (KVA): 75  
Frequency (Hz): 50  
Voltage (V): 230 / 400  
Engine rpm (rpm): 1500  
Alternator: MECC ALTE ECP32-3L/4  
Poles: 4  
Protection degree: IP23  
PTO speed (round/min): 420  
Required tractor power: 150 Hp  
Length (mm): 1140  
Width (mm): 750  
Height (mm): 1065  
Dry weight (Kg): 454  
Silenced: No  
Super silenced: No  
Voltage regulator: AVR

