

# MOSA GE SX-16000 KDM

Product price:

**6.750,00 € tax excluded**



## Product description:

MOSA GE SX-16000 KDM 14,4 KW

MOSA GE SX-16000 KDM singlephase 14,4 KW generator set with Kohler diesel engine. The MOSA GE SX-16000 KDM generator set is equipped with electric start. The alternator of the MOSA GE SX-16000 KDM generator set is synchronous and singlephase.

This MOSA is compact and convenient to maneuver and transport thanks to its compact size, its weight of 372 kg as well as the practical central hook for lifting.

The MOSA GE SX-16000 KDM generator set with 38-liter fuel tank has a fuel consumption of 3,7 liters/hour at 75% load for an autonomy of more than 10 hours.

## Sockets:

1 x 230V 63A 2P+T CEE IP67

1 x 230V 32A 2P+T CEE IP67

1 x 230V 16A 2P+T CEE IP67

1 x 230V 16A 2P+T SCHUKO

## Technical specifications MOSA GE SX-16000 KDM:

Maximum power Single-phase: 14.4 KW

Single-phase continuous use power: 13 KW

Maximum power Single-phase: 16 KVA

Single-phase continuous use power: 14.5 KVA

Fuel: Diesel

Voltage: 230 V

Frequency: 50 Hz

Engine: Kohler KDW1003

Starting: Electric

Consumption: 3.7 Lt/h at 75% of the load

Length: 1784 mm

Width: 710 mm  
Height: 1115 mm  
Weight: 372 Kg  
Supersilenced

MOSA GE SX-16000 KDM portable generator set - Kohler diesel engine electric start - Singlephase alternator

If you are looking for another product such as MOSA GE SX-16000 KDM generator set then you can browse our catalog for more terrestrial generator sets.

Images and technical data are not binding.

**Product features:**

Phase: Single phase  
Maximum power single phase (KW): 14.4  
Continuous power single phase (KW): 13  
Maximum power single phase (KVA): 16  
Continuous power single phase (KVA): 14.5  
Fuel: Diesel  
Frequency (Hz): 50  
Voltage (V): 230  
Sockets configuration: 1 x 230V 63A 2P+T CEE IP67 - 1 x 230V 32A 2P+T CEE IP67 - 1 x 230V 16A 2P+T CEE IP67 - 1 x 230V 16A 2P+T SCHUKO  
Engine: Kohler KDW1003  
Emissions Regulations: Stage 5  
Engine rpm (rpm): 3000  
Starting system: Electric  
Alternator: Synchronous  
Fuel tank capacity (L): 38  
Consumption (L/h): 3..7  
Running time (h): 10.5  
Acoustic pressure: 62 dB(A) at 7 m  
Length (mm): 1784  
Width (mm): 710  
Height (mm): 1115  
Silenced: Yes  
Super silenced: Yes  
Product type: Generator  
ATS Switch device : Optional  
Voltage regulator: AVR  
Engine manufacturer: Kohler

