



# MASE MARINER 1304 S SINGLE PHASE MARINE GENERATOR SILENCED 12KW

## Product description:

MASE MARINER 1304 S SILENCED SINGLE-PHASE MARINE GENERATOR 12KW

MASE MARINER1304S single-phase silenced marine generator is equipped with a YANMAR 3TNV88 diesel engine capable of delivering a maximum power of 12 KW at 1800 rpm.

The MASE MARINER1304S is built with and synchronous alternator, self-excited with air cooling, is extremely compact and powerful, suitable even on small boats. The alternator is complete with a voltage regulator that ensures the stability of the voltage delivered by the generator, delivering current like that of the house.

The MASE MARINER1304S allows easy access for maintenance of the power and lubrication systems, sea water pump, air filter, oil filter and fuel. It is also equipped with safety systems of auto stop for low oil pressure and high temperature engine or exhaust gas.

The MASE MARINER1304S is equipped with a soundproof cabin that makes it super silent, with a sound emission of 54dB(A) at a distance of 7 m. The painted aluminum soundproof cabin is extremely lightweight and of very high resistance to external agents.

## TECHNICAL FEATURES MASE MARINER1304S

Phase Type: Single Phase

Maximum Power: 12 KW

Fuel: Diesel

Voltage: 120 - 240 V

Frequency: 60 Hz

Motor: YANMAR 3TNV88, 4 Stroke

Mechanical Power: 20.4 Hp

Number of Cylinders: 3

Displacement: 1642 cc  
Engine RPM: 1800 rpm  
Fuel Consumption: 4 l/h  
Sound Pressure: 54 dB(A) @ 7 m  
Alternator: Synchronous Brushless  
Voltage Regulator: Yes  
Length: 1040 mm  
Width: 631 mm  
Height: 694 mm  
Weight: 344 Kg

If you are looking for another marine generator then you can browse the entire catalog of marine generators.

Images and technical data are not binding.

#### **Product features:**

Phase: Single phase  
Maximum power single phase (KW): 12  
Fuel: Diesel  
Frequency (Hz): 60  
Voltage (V): 120 / 240  
Engine: YANMAR 3TNV88  
Engine rpm (rpm): 1800  
Speed governor: Centrifugal, mechanical  
Engine capacity (cm<sup>3</sup>): 1642  
Number cylinders: 3  
Cooling: Air  
Inyección : Direct  
Alternator: Synchronous, self-excited  
Poles: 4  
Lubrication: Forced  
Consumption (L/h): 4 at 100% of the load  
Acoustic pressure: 53 dB(A) at 7 m  
Length (mm): 1040  
Width (mm): 631  
Height (mm): 694  
Dry weight (Kg): 344  
Inverter: No  
AVR: No  
Compound: No  
Silenced: Yes

---

Super silenced: Yes  
Voltage regulator: YES