



# MASE MARINER 1460 KS SINGLE PHASE MARINE GENERATOR SILENCED 14.6KW

## Product description:

MASE MARINER 1460 KS SILENCED SINGLE-PHASE MARINE GENERATOR 12KW

MASE MARINER1460KS single phase silenced marine generator is equipped with a KUBOTA D1703 diesel engine capable of delivering a maximum power of 14.6 KW at 1800 rpm.

The MASE MARINER1460KS is equipped with a soundproof cabin that makes it super silent, with a sound emission of 52dB(A) at a distance of 7 m. The painted aluminum soundproofing cabin is extremely lightweight and of very high resistance to external agents.

The MASE MARINER1460KS allows easy access for maintenance of the fuel and lubrication systems, sea water pump, air filter, oil filter and fuel. It is also equipped with safety systems of auto stop for low oil pressure and high engine temperature or exhaust gas.

The alternator of the MASE MARINER1460KS is synchronous with 4 poles, self-regulated, self-excited, brushless, which in coupling with the powerful KUBOTA engine can deliver a maximum power of 14.6 KW. The alternator is complete with a voltage regulator that ensures the stability of the voltage delivered by the generator, delivering current like that of the house.

## Technical Features MASE MARINER1460KS

Phase Type: Single Phase

Maximum Power: 14.6 KW

Fuel: Diesel

Voltage: 120 - 240 V

Frequency: 60 Hz

Engine: KUBOTA D1703, 4 Stroke

Mechanical Power: 24.3 Hp

Number of Cylinders: 3

Displacement: 1500 cc  
Engine RPM: 1800 rpm  
Fuel Consumption: 4.5 l/h  
Sound pressure: 52 dB(A) @ 7 m  
Alternator: Synchronous Brushless  
Voltage regulator: Yes  
Length: 1040 mm  
Width: 631 mm  
Height: 694 mm  
Weight: 390 Kg

If you are looking for another marine generator then you can browse the entire catalog of marine generators.

Images and technical data are not binding.

#### **Product features:**

Phase: Single phase  
Maximum power single phase (KW): 14.64  
Fuel: Diesel  
Frequency (Hz): 60  
Voltage (V): 120 / 240  
Engine: KUBOTA D1703  
Engine rpm (rpm): 1800  
Speed governor: Centrifugal, mechanical  
Engine capacity (cm<sup>3</sup>): 1500  
Number cylinders: 3  
Cooling: Air  
Inyección : Indirect  
Alternator: Synchronous, self-excited  
Poles: 4  
Lubrication: Forced  
Consumption (L/h): 4.5  
Acoustic pressure: 52 dB(A) at 7 m  
Length (mm): 1040  
Width (mm): 631  
Height (mm): 694  
Dry weight (Kg): 390  
Inverter: No  
AVR: No  
Compound: No  
Silenced: Yes

---

Super silenced: Yes  
Voltage regulator: YES