



MASE MARINER 1960 KS SINGLE PHASE MARINE GENERATOR SILENCED 20KW EPA

Product price:

11.209,00 € tax excluded

Product description:

MASE MARINER 1960 KS SILENCED SINGLE-PHASE MARINE GENERATOR 20 KW EPA

MASE MARINER1960KS single-phase silenced marine generator is equipped with a KUBOTA V2203 engine with **EPA emissions standard**, powered by diesel and capable of delivering a maximum power of 20 KW at 1800 rpm.

The MASE MARINER1960KS alternator is a 4-pole synchronous, self-regulated, self-excited, brushless alternator, which in combination with the powerful KUBOTA engine can deliver a maximum power of 20 KW. The alternator is complete with AVR voltage regulator that ensures the stability of the voltage delivered by the generator, delivering current like the one at home.

The MASE MARINER1960KS allows easy access for maintenance of the power and lubrication systems, seawater pump, air filter, oil filter and fuel. It is also equipped with safety systems of auto stop for low oil pressure and high temperature engine or exhaust gas.

The MASE MARINER1960KS is equipped with a soundproof cabin that makes it super silent, with a sound emission of 51dB(A) at a distance of 7 m. The painted aluminum soundproofing cabin is extremely lightweight and of very high resistance to external agents.

The MASE MARINER1960KS marine generator has **EPA certification** valid only **for the US market**.

TECHNICAL FEATURES MASE MARINER1960KS

Phase Type: Single Phase

Maximum Power: 20 KW

Fuel: Diesel

Voltage: 120 - 240 V
Frequency: 60 Hz
Engine: KUBOTA V2203, 4 Stroke
Mechanical Power: 36.5 Hp
Number of Cylinders: 4
Displacement: 2197 cc
Engine RPM: 1800 rpm
Fuel Consumption: 6.5 l/h
Sound pressure: 51 dB(A) @ 7 m
Alternator: Synchronous Brushless
Voltage regulator: AVR
Length: 1135 mm
Width: 631 mm
Height: 694 mm
Weight: 465 Kg
Emissions regulations: EPA

If you are looking for another marine generator then you can browse the entire catalog of marine generators.

Images and technical data are not binding.

Product features:

Phase: Single phase
Maximum power single phase (KW): 20
Continuous power single phase (KW): 18
Fuel: Diesel
Frequency (Hz): 60
Voltage (V): 120 / 240
Engine: KUBOTA V2203
Emissions Regulations: EPA
Engine rpm (rpm): 1800
Speed governor: Electronic
Engine capacity (cm³): 2197
Number cylinders: 4
Cooling: Air
Inyección : Indirect
Alternator: Synchronous, self-excited
Poles: 4
Consumption (L/h): 6.5
Acoustic pressure: 51 dB(A) at 7 m
Length (mm): 1135

Width (mm): 631
Height (mm): 694
Dry weight (Kg): 465
Inverter: No
AVR: Yes
Silenced: Yes
Super silenced: Yes
Voltage regulator: AVR