



ITALTOWER OKAPI PRO04 LIGHTING TOWER 6X160W MULTILED WITH GENERATOR

Product price:

12.239,00 € tax excluded

Product description:

ITALTOWER OKAPI PRO04 LIGHTING TOWER 6x160 W MULTILED WITH GENERATOR

The ITALTOWER OKAPI PRO04 Light Tower is equipped with a Yanmar 2TNV70 Diesel powered engine, capable of delivering a power of 3.5KW to serve 6 LED 160W.

The ITALTOWER OKAPI PRO04 MULTILED is equipped with a hydraulic lifting system, capable of raising the tower to a height of 8.5 m. Thanks to the 6 LED lights ITALTOWER OKAPI PRO04 is able to illuminate an area of 4200 square meters with a maximum luminous intensity of 122100 lm.

The ITALTOWER OKAPI is equipped with a Yanmar 2TNV70 engine, fully compliant with the latest European regulations on emissions. Moreover, the light tower has the possibility to be powered by an external network thanks to the 16 A 230 V socket and plug present on the machine. By means of an internal selector, the operator will decide whether to power the LEDs from the external network present on the work site or from the Stage V generator present in the tower.

The 6 powerful 160 W lights together with its compact design allow to optimize any space making ITALTOWER OKAPI a product of high quality and effectiveness. The 4 stabilizers also make it wind resistant up to 110 km/h and ideal for any surface.

TECHNICAL FEATURES ITALTOWER OKAPI PRO04

Number of lights: 6
Lamps power: 160 W LED
Lumen: 122100 lm
Illuminated area: 4200 sqm



Phase type: Single phase
Maximum power: 3.5 KW
Sound Pressure: 61dB(A) @ 7m
Voltage: 230 V
Frequency: 50 Hz
Control Unit: DeepSea L401 MKII
Auxiliary Power: 1.2 kVA
Motor: Yanmar 2TNV70
RPM: 1500rpm
Refrigerant: Liquid
Emissions Standard: Stage V
Alternator: Linz Alumen
Tank Capacity: 120 l
Fuel: Diesel
Fuel Consumption: 0.55 l/h
Maximum Height: 8.5m
Lifting System: Hydraulic
Rotation: 350°
Wind resistance: 110 Km/h
Stabilizers 4 + 1
Length (mm): 2370
Width (mm): 1470
Height (mm): 2400
Dry weight (Kg): 850

Looking for a light tower with different features? Here you can find the full range of lighting towers ITALTOWER or other specialized brands.

Images and technical data are not binding and may be subject to revisions by the manufacturer

Product features:

Phase: Single phase
Maximum power single phase (KW): 3.5
Fuel: Diesel
Frequency (Hz): 50
Voltage (V): 230
Engine: Yanmar 2TNV70
Emissions Regulations: Stage 5
Engine rpm (rpm): 1500
Cooling: Liquid
Alternator: Linz Alumen SB
Type of lamps: MULTILED

Lamps: 6 x 160 W
Telescopic pole: Vertical
Illuminated area (m²): 4200
Total lumens (Lm): 122100
Lifting System: Hydraulic lifting system
Maximum height (m): 8.5
Mast rotation: 355°
Open size (mm): 2370 x 1470 x 8500
Length closed (mm): 2350
Width closed (mm): 1460
Height closed (mm): 2400
With generator / Without generator: With generator
Transportability: Stationary
Stability to wind (Km/h): 110
Fuel tank capacity (L): 120
Consumption (L/h): 0.55
Acoustic pressure: 61 dB(A) at 7.5 m
Weight (Kg): 855