



# ITALTOWER OKAPI PRO04 LIGHTING TOWER 6X160W MULTILED WITH GENERATOR

**Product price:**

**12.239,00 € tax excluded**

## **Product description:**

ITALTOWER OKAPI PRO04 LIGHTING TOWER 6x160 W MULTILED WITH GENERATOR

The ITALTOWER OKAPI PRO04 Light Tower is equipped with a Yanmar 2TNV70 Diesel powered engine, capable of delivering a power of 3.5KW to serve 6 LED 160W.

The ITALTOWER OKAPI PRO04 MULTILED is equipped with a hydraulic lifting system, capable of raising the tower to a height of 8.5 m. Thanks to the 6 LED lights ITALTOWER OKAPI PRO04 is able to illuminate an area of 4200 square meters with a maximum luminous intensity of 122100 lm.

The ITALTOWER OKAPI is equipped with a Yanmar 2TNV70 engine, fully compliant with the latest European regulations on emissions. Moreover, the light tower has the possibility to be powered by an external network thanks to the 16 A 230 V socket and plug present on the machine. By means of an internal selector, the operator will decide whether to power the LEDs from the external network present on the work site or from the Stage V generator present in the tower.

The 6 powerful 160 W lights together with its compact design allow to optimize any space making ITALTOWER OKAPI a product of high quality and effectiveness. The 4 stabilizers also make it wind resistant up to 110 km/h and ideal for any surface.

## TECHNICAL FEATURES ITALTOWER OKAPI PRO04

Number of lights: 6  
Lamps power: 160 W LED  
Lumen: 122100 lm  
Illuminated area: 4200 sqm



Phase type: Single phase  
Maximum power: 3.5 KW  
Sound Pressure: 61dB(A) @ 7m  
Voltage: 230 V  
Frequency: 50 Hz  
Control Unit: DeepSea L401 MKII  
Auxiliary Power: 1.2 kVA  
Motor: Yanmar 2TNV70  
RPM: 1500rpm  
Refrigerant: Liquid  
Emissions Standard: Stage V  
Alternator: Linz Alumen  
Tank Capacity: 120 l  
Fuel: Diesel  
Fuel Consumption: 0.55 l/h  
Maximum Height: 8.5m  
Lifting System: Hydraulic  
Rotation: 350°  
Wind resistance: 110 Km/h  
Stabilizers 4 + 1  
Length (mm): 2370  
Width (mm): 1470  
Height (mm): 2400  
Dry weight (Kg): 850

Looking for a light tower with different features? Here you can find the full range of lighting towers ITALTOWER or other specialized brands.

Images and technical data are not binding and may be subject to revisions by the manufacturer

**Product features:**

Phase: Single phase  
Maximum power single phase (KW): 3.5  
Fuel: Diesel  
Frequency (Hz): 50  
Voltage (V): 230  
Engine: Yanmar 2TNV70  
Emissions Regulations: Stage 5  
Engine rpm (rpm): 1500  
Cooling: Coolant Liquid  
Alternator: Linz Alumen SB  
Type of lamps: MULTILED

---

Lamps: 6 x 160 W  
Telescopic pole: Vertical  
Illuminated area (m<sup>2</sup>): 4200  
Total lumens (Lm): 122100  
Lifting System: Hydraulic lifting system  
Maximum height (m): 8.5  
Mast rotation: 355°  
Open size (mm): 2370 x 1470 x 8500  
Lenght closed (mm): 2350  
Width closed (mm): 1460  
Height closed (mm): 2400  
With generator / Without generator: With generator  
Transportability: Stationary  
Stability to wind (Km/h): 110  
Fuel tank capacity (L): 120  
Consumption (L/h): 0.55  
Acoustic pressure: 61 dB(A) at 7.5 m  
Weight (Kg): 855