



# ITALTOWER ASTRID PRO05 LIGHTING TOWER 6x320 W MULTILED WITH HOMOLOGATED TROLLEY AND GENERATOR

**Product price:**

**15.739,00 € tax excluded**

## **Product description:**

ITALTOWER ASTRID PRO05 LIGHT TOWER 6x320 W MULTILED WITH APPROVED TROLLEY AND GENERATOR

The ITALTOWER ASTRID PRO05 Light Tower is equipped with a Yanmar 3TNM68 Diesel powered engine, capable of delivering a power of 3.5KW to serve 6 LED lamps 320W.

The ITALTOWER ASTRID PRO05 MULTILED is equipped with a hydraulic lifting system, capable of raising the tower to a height of 8.5 m. Thanks to the 6 LED lamps ITALTOWER ASTRID PRO05 is able to illuminate an area of 7800 square meters with a maximum luminous intensity of 249200 lm.

The ITALTOWER ASTRID PRO03 is equipped with a Yanmar 3TNM68 Stage V engine, fully compliant with the latest European regulations on emissions. Moreover, the ITALTOWER ASTRID PRO05 has the possibility to be powered by an external network thanks to the 16 A 230 V socket and plug present on the machine. By means of an internal selector, the operator can decide whether to power the LEDs from the external power supply present in the work site or from the Stage V generator present in the tower.

The handling of the ITALTOWER ASTRID PRO05 is easier both during transport and storage thanks to the 6 forks for forklift available in the base of the light tower. In the upper part of the carpentry there are 3 eyebolts for an optimal lifting of the tower by means of a crane, in addition it is also equipped with a Ø 50mm ball towing hook.

---

## TECHNICAL FEATURES OF ITALTOWER ASTRID PRO05

Number of lights: 6  
Lamps power: 320 W LED  
Lumen: 249200 lm  
Illuminated area: 7800 sqm  
Phase type: Single phase  
Maximum power: 3.5 KW  
Sound Pressure: 61dB(A) @ 7m  
Voltage: 230 V  
Frequency: 50 Hz  
Control Unit: DeepSea L401 MKII  
Auxiliary Power: 1.2 kVA  
Motor: Yanmar 3TNM68  
RPM: 1500rpm  
Coolant: Liquid  
Emissions Standard: Stage V  
Alternator: Linz Alumen  
Tank capacity: 120 l  
Fuel: Diesel  
Fuel consumption: 0.55 l/h  
Maximum height: 8.5m  
Lifting system: Hydraulic  
Rotation: 350°  
Wind resistance: 110 Km/h  
Trolley: Road trolley (EU standard)  
Stabilizers 4 + 1 (wheels)  
Length (mm): 2370  
Width (mm): 1470  
Height (mm): 2400  
Dry weight (Kg): 850

Looking for a light tower with different features? Here you can find the full range of towers ITALTOWER or other specialized brands.

Images and technical data are not binding and may be subject to revisions by the manufacturer

### **Product features:**

Phase: Single phase  
Maximum power single phase (KW): 3.5  
Fuel: Diesel  
Frequency (Hz): 50

---

Voltage (V): 230  
Engine: Yanmar 3TNM68  
Emissions Regulations: Stage 5  
Engine rpm (rpm): 1500  
Engine capacity (cm<sup>3</sup>): 686  
Number cylinders: 2  
Cooling: Coolant Liquid  
Alternator: Linz Alumen SB  
Type of lamps: MULTILED  
Lamps: 6 x 320 W  
Telescopic pole: Vertical  
Illuminated area (m<sup>2</sup>): 7800  
Total lumens (Lm): 249300  
Lifting System: Hydraulic lifting system  
Maximum height (m): 8.5  
Mast rotation: 350°  
Lenght closed (mm): 2350  
Width closed (mm): 1400  
Height closed (mm): 2400  
With generator / Without generator: With generator  
Transportability: Fast Trailer  
Stability to wind (Km/h): 110  
Fuel tank capacity (L): 120  
Consumption (L/h): 0.55  
Acoustic pressure: 61 dB(A) at 7.5 m  
Weight (Kg): 855