



ITALTOWER PEGASO PRO02 LIGHTING TOWER 4x75 W MULTILED WITH HAND CART AND GENERATOR

Product price:

3.464,00 € tax excluded

Product description:

ITALTOWER PEGASO PRO01 LIGHTER TOWER 4x75 W MULTILED WITH HAND CART AND GENERATOR

ITALTOWER PEGASO PRO02 Light Tower is equipped with an Arion 6000 engine powered by gasoline, capable of delivering a power of 4.8KW at the service of 4 LED lamps of 75W.

The ITALTOWER PEGASO PRO02 is a compact and easy to use, with its handy trolley you can move it anywhere. Ideal for bringing light in remote areas or open countryside where there is poor lighting.

Thanks to 4 LED projectors ITALTOWER PEGASO PRO02 can illuminate an area of 1500 square meters with a maximum luminous intensity of 36900 lm. ITALTOWER PEGASO PRO02 is supplied with two retractable handles for easy transport even on uneven ground and with 3 stabilizers (2 front and 1 rear) for optimal stabilization.

TECHNICAL FEATURES ITALTOWER PEGASO PRO02

Number of lights: 4

Lamps power: 75 W LED

Lumen: 36900 lm

Lit area: 1500 square meters

Phase type: Single-phase

Maximum power: 4.8 KW

Sound pressure: 70dB(A) @ 7m

Voltage: 230 V



Frequency: 50 Hz
Auxiliary power supply: 3.2 kVA
Motor: Arion 6000
RPM: 3000rpm
Coolant: Air
Emission regulations: Not Emitted
Alternator: Arion 6000
Tank Capacity: 25 l
Fuel: Gasoline
Autonomy: 27 h
Fuel Consumption: 0.9 l/h
Maximum Height: 5.5m
Lifting System: Manual
Rotation: 350°
Wind Resistance: 80 Km/h
Trolley: Hand Towing
Outriggers: 2
Length (mm): min 1300 - Max 1300
Width (mm): min 560 - Max 800
Height (mm): min 2380 - Max 5500
Dry Weight (Kg): 250

Are you looking for a light tower with different characteristics? Here you can find the full range of towers ITALTOWER or other specialized brands.

Images and technical data are not binding and may be subject to revisions by the manufacturer

Product features:

Phase: Single phase
Maximum power single phase (KW): 4.8
Fuel: Gasoline
Frequency (Hz): 50
Voltage (V): 230
Engine: Arion 6000
Emissions Regulations: Stationary Use
Engine rpm (rpm): 3000
Number cylinders: 1
Cooling: Air
Alternator: Arion 6000
Type of lamps: MULTILED
Lamps: 4 x 75 W
Telescopic pole: Vertical



Illuminated area (m²): 1500
Total lumens (Lm): 36900
Lifting System: Manual lifting system
Maximum height (m): 5.5
Mast rotation: 350°
Open size (mm): 1300 x 800 x 5500
Length closed (mm): 1300
Width closed (mm): 560
Height closed (mm): 2380
With generator / Without generator: With generator
Transportability: Wheels and handles
Stability to wind (Km/h): 80 Km/h
Fuel tank capacity (L): 25
Consumption (L/h): 0.9
Acoustic pressure: 70 dB(A) at 7 m
Voltage regulator: AVR
Weight (Kg): 250