



# ITALTOWER TOWERLOOP PRO02 LIGHT TOWER 4x75W MULTILED

**Product price:**

**3.740,00 € tax excluded**

## **Product description:**

### ITALTOWER TOWERLOOP PRO02 LIGHT TOWER 4x75W MULTILED

ITALTOWER TOWERLOOP PRO02 is a light tower equipped with 4 led projectors 75W high brightness with directional optics and handles for easy rotation, with a lifting system that allows an extension up to 7 mt.

The ITALTOWER TOWERLOOP PRO02 light tower is supplied with a plug socket kit for the connection in series of several units up to a maximum of 6. The ITALTOWER TOWERLOOP PRO02 is supplied with galvanized guides and eyebolts for moving and lifting. These features make the operation by the operator very simple, making the unit easy to handle and use.

The efficient manual lifting system is able to bring the projectors to a height of 7 m, combined with 4 LED lamps, the light tower can illuminate an area of 2000 square meters with a maximum luminous intensity of 36900 lm.

The ITALTOWER TOWERLOOP PRO02 is equipped with 4 stabilizers which make the light tower resistant to strong wind gusts up to 100 km/h. ITALTOWER TOWERLOOP PRO02 is NOT equipped with an internal generator, but in return it can be effectively powered by an external source such as a generator set or can be connected directly to the power grid.

### ITALTOWER TOWERLOOP PRO02 TECHNICAL FEATURES

Number of luminaires: 4

Lamp wattage: 75 W multiLED

Lumen: 36900 lm

Illuminated area: 2000 square metres

Phase type: Single phase



Voltage: 110 / 230 V  
Frequency: 50 Hz (60 Hz ONLY ON REQUEST)  
Output: 230 V 16A  
Maximum height: 7 m  
Lifting system: Manual  
Rotation: 359°  
Wind resistance: 100 Km/h  
Trolley: Hand-drawn trolley  
Stabilisers: 4  
Length (mm): min 930 - MAX 1800  
Width (mm): min 800 - MAX 1600  
Height (mm): min 2300 - Max 7000  
Dry weight (Kg): 235

Are you looking for a light tower with different characteristics? Here you can find the full range of light towers ITALTOWER or other specialized brands.

Images and technical data are not binding and may be subject to revision by the supplier.

#### **Product features:**

Phase: Single phase  
Frequency (Hz): 50  
Voltage (V): 110 / 230  
Type of lamps: MULTILED  
Lamps: 4 x 75 W  
Telescopic pole: Vertical  
Illuminated area (m²): 2000  
Lifting System: Manual lifting system  
Maximum height (m): 7  
Mast rotation: 359°  
Open size (mm):  
Length closed (mm): 930  
Width closed (mm): 800  
Height closed (mm): 2300  
With generator / Without generator: Without generator  
Transportability: Stationary  
Stability to wind (Km/h): 100 Km/h  
Weight (Kg): 235

