



# ITALTOWER KT55 LIGHTING TOWER 4x160 W MULTILED

**Product price:**

**1.827,00 € tax excluded**

## **Product description:**

### ITALTOWER KT55 LIGHTER TOWER 4x160 W MULTILED

ITALTOWER KT55 4x160W is a manually lifted light tower equipped with 4 floodlights capable of delivering a light output of 160W each.

ITALTOWER KT55 4x160 is equipped with a galvanized steel lifting tower capable of extending up to a maximum height of 5.5 meters. The tower is equipped with a winch that allows the manual lifting of the telescopic pole in safety thanks to an iron cable made up of 133 anti-twisting micro-cables improving the resistance and the capacity of the winch itself.

The peculiarity of the tower is the fact that it is equipped with a winch that allows the manual lifting of the telescopic pole in safety thanks to an iron cable made up of 133 anti-twisting micro-cables improving the resistance and the capacity of the winch itself.

The particularity of the ITALTOWER KT55, are the 4 fixing holes at the base that allows it to be applied on generator sets or external supports and a rotation of the pole of 360°.

The ITALTOWER MT55 is suitable for a variety of large-scale construction work, maintenance repair, accident management and disaster relief work, high brightness lighting needs.

ITALTOWER KT55 4x160 is designed to be combined with a generator set and can be connected in series in order to use one generator for multiple lighting units.

### ITALTOWER KT55 4x160 TECHNICAL FEATURES

Number of lights: 4  
Lamps power: 160 W LED  
Lumen: 81400 lm  
Illuminated area: 2400 sqm



Voltage: 230 V  
Frequency: 50 Hz  
Consumption: 4x160W = 0.64 KW  
Maximum height: 5.5 m  
Lifting system: Manual  
Wind resistance: 80 Km/h  
Trolley: Stationary  
Stabilizers: Bolt-on base  
Length (mm): 640  
Width (mm): 350  
Height (mm): 2089  
Dry weight (Kg): 90

Looking for a light tower with different technical characteristics? Here you can find the full range of light towers ITALTOWER or other brands specializing in the sector.

Images and technical data are not binding and may be subject to revisions by the manufacturer.

**Product features:**

Frequency (Hz): 50  
Voltage (V): 230  
Type of lamps: LED  
Lamps: 4 x 160 W  
Telescopic pole: Vertical  
Illuminated area (m<sup>2</sup>): 2400  
Total lumens (Lm): 81400  
Lifting System: Manual lifting system  
Maximum height (m): 5.5  
Length closed (mm): 350  
Width closed (mm): 640  
Height closed (mm): 2089  
With generator / Without generator: Without generator  
Transportability: Stationary  
Stability to wind (Km/h): 80 Km/h  
Weight (Kg): 90