



AURORA LIGHT TOWER ALPHA K2-L 4X160 - F FAST TOWING TROLLEY

Product description:

AURORA LIGHTHOUSE TOWER ALPHA K2-L 4X160 - F F FAST TOWING TROLLEY

AURORA ALPHA K2-L 4X160 - F is a light tower with a generator equipped with a Kohler 15LD350 diesel engine and a manual hoisting winch equipped with 4 floodlights capable of delivering a light output of 160W each.

AURORA ALPHA K2-L 4X160 - F is equipped with a galvanized steel lifting system capable of extending up to a maximum height of 8.5 meters, including 4 stabilization feet to secure the light tower once opened. The lifting system is operated manually and by a hydraulic system that allows the maximum extension without effort.

AURORA ALPHA K2-L 4X160 - F is complete with Kohler 15LD350 engine, these engines are super efficient with 3000 rpm. THE AURORA ALPHA K2-L 4X160 - F TOWERS besides guarantee you an autonomy of 180 h of work at 30% of the load.

The AURORA light tower lenses feature extremely special optics designed specifically for the civil engineering and construction industries. This innovative fully directional LED lens design ensures maximization of light spread and reduction of waste.

A single AURORA ALPHA can cover an area of 3300 m², ensuring a brighter, safer and more productive site.

AURORA ALPHA comes complete with a fast trolley, this gives the customer the ability to easily transport the light tower.

TECHNICAL FEATURES AURORA ALPHA K2-L 4X160 - F

Manufacturer: Green Power
Projectors: 4 160W LEDs

Lighted Area: 3300 Sq Ft
Max Height: 8.5 Mt
Lift: Manual
Motor: Kohler 15LD350
Emissions: Stage V
Power supply: Diesel
Engine speed: 3000 rpm
Telescopic pole: Galvanized steel
Wind resistance max: 100 Km/h
Wind stability: nr 4 stabilizers
Transport: Fast towing trolley
Noise level at 7 mt: 70 dB (A)
Total lumens: 81400 lm
Voltage: 230V
Frequency: 50 Hz
Autonomy 30% load: 180 hr
Closed tower dimensions: 1154x1118x2430 mm
Open tower dimensions: 2030x2202x8500 mm
Dry weight: 560 Kg

Looking for a product with different characteristics? Here you can find the full range Green Power or other specialized brands.

Images and technical data are not binding and may be subject to revision by the supplier.

Product features:

Fuel: Diesel
Frequency (Hz): 50
Voltage (V): 230
Emissions Regulations: Stage 5
Starting system: Electric
Type of lamps: LED
Lamps: 4 x 160W
Telescopic pole: Galvanized steel
Illuminated area (m²): 3300
Lifting System: Hydraulic lifting system
Maximum height (m): 8.5
Mast rotation: 359°
Open size (mm): 2030x2202x8500 mm
Closed size (mm): 1154x1118x2430 mm
Dry weight (Kg): 560
Engine manufacturer: Kohler 15LD350

Trailer type : Fast towing