

AURORA LIGHT TOWER BETA YX-L 4X320 -S WITH SLOW TOWING TROLLEY



Product description:

AURORA TORRE FARO BETA YX-L 4X320 -S WITH TOWING TROLLEY

AURORA BETA YX-L 4X320 -S is a light tower with generator equipped with Yanmar 3TNV68 Diesel engine and hydraulic lifting equipped with 4 floodlights capable of delivering a light output of 320W each.

AURORA BETA YX-L 4X320 -S is equipped with a galvanized steel lifting tower capable of extending up to a maximum height of 8.5 meters, including 4 stabilization feet to secure the light tower once opened. The lifting system is operated manually and by a hydraulic system that allows the maximum extension without effort.

AURORA BETA YX-L 4X320 -S is equipped with Yanmar 3TNV68 Diesel engine, this engine is super efficient with 1500 rpm. The AURORA BETA YX-L 4X320 -S in addition guarantee you a range of 218 h of work at 30% load.

The AURORA light tower lenses feature extremely special optics designed specifically for the civil engineering and construction sectors. This innovative fully directional LED lens design ensures maximization of light spread and reduction of waste.

A single AURORA BETA tower can cover an area of 5000 m², ensuring a brighter, safer and more productive site.

The safety stop stops the descent at a safe height that avoids the risk of collisions with the projectors during the normal descent phase or in case of sudden breakage of the telescopic ropes or the automatic brake of the lifting winch. Thanks to the low weight and the set-up on a manual towing trolley, it can be easily manoeuvred by a single operator.

AURORA BETA YX-L 4X320 -S is supplied complete with fast towing trolley complete with

autonomous braking system, complete with rear lights with integrated reverse light and all the features for a proper urban and extra-urban transport.

TECHNICAL CHARACTERISTICS AURORA BETA YX-L 4X320 -S

Manufacturer: Green Power
Projectors: 4 320W LEDs
Lighted Area: 5000 Square Meter
Max Height: 8.5 Mt
Lift: Hydraulic
Engine: Yanmar 3TNV68
Emissions: Stage V
Fueling: Diesel
Engine RPM: 1500 rpm
Telescopic Pole: Galvanized steel
Max Wind Resistance: 110 Km/h
Wind Stability: nr 4 stabilizers
Transport: Slow Towing Trolley
Noise level at 7 mt: 61 dB (A)
Total lumens: 166200 lm
Voltage: 230V
Frequency: 50 Hz
Autonomy 30% load: 75 hr
Closed tower dimensions: 2370x1473x2353 mm
Open tower dimensions: 2370x1818x8500 mm
Dry weight: 900 Kg

Looking for a product with different characteristics? Here you can find the full range Green Power or other specialized brands.

Images and technical data are not binding and may be subject to revisions by the manufacturer

Product features:

Fuel: Diesel
Frequency (Hz): 50
Voltage (V): 230
Engine rpm (rpm): 1500
Starting system: Electric
Type of lamps: LED
Lamps: 4 x 320W
Telescopic pole: Galvanized steel
Illuminated area (m²): 5000

Total lumens (Lm): 166200
Lifting System: Hydraulic lifting system
Maximum height (m): 8.5
Mast rotation: 350°
Open size (mm): 2370x1818x8500
Closed size (mm): 2370x1473x2353
With generator / Without generator: With generator
Transportability: Slow Trailer
Stability to wind (Km/h): 110
Running time (h): 75 al 30 % del carico
Acoustic pressure: 61 dB(A) at 7 m
Dry weight (Kg): 900
Engine manufacturer: Yanmar 3TNV68