

# CGM 250P-B300 WITH AUTOMATIC CONTROL PANEL



**Product price:**

**36.650,00 € tax excluded**

## **Product description:**

CGM 250P-B300 Single/three-phase 250KVA generator with automatic control panel

The CGM 250P-B300 is a single/three phase 250KVA generator with a 1500 rpm Perkins diesel engine, compact and easy to use, mounted on a fixed base. This CGM 250P-B300 generator is in an open version and is easy to handle and transport thanks to its base with pivoting feet.

The CGM 250P-B300 generator consists of a Stamford, Mecc Alte or Marelli Motori, self-excited, brushless alternator with AVR voltage regulator. The CGM 250P-B300 generator is equipped with an electric starter with a low fuel consumption battery, consuming only 41,5 litres per hour at 75% load. In addition, it has a control panel with automatic control unit and terminal box for automatic start-up.

This generator is perfect for use outdoors, such as on construction sites.

The CGM 250P-B300 generator is part of the Industrial range and is characterised by its versatility for installation in urban environments such as shops or shopping centres, for the telecommunications environment, for military applications and much more.

## **Technical characteristics of the CGM 250P-B300 generator:**

Phase type: Single-phase / Three-phase

Maximum three-phase power: 220 KW / 275 KVA

Three-phase continuous power: 200 KW / 250 KVA

Maximum single-phase power: 73.33 KW / 91.67 KVA

Single-phase continuous use power: 66.67 KW / 83.33 KVA

Fuel: Diesel

Voltage: 230 V / 400 V

Frequency: 50 Hz

Motor: PERKINS 1206A-E70TTAG3

Engine speed: 1500 rpm

Starting: Electric

Consumption: 41.5 Lt/h at 75% load

Length: 2800 mm

Width: 1310 mm  
Height: 1800 mm  
Weight: 2115 Kg  
AVR

If you are looking for a product like the CGM 250P-B300 then you can browse the full range of CGM generators or other types of products in our catalogue to find the one that best suits your needs.

Images and technical data are not binding.

**Product features:**

Phase: Single phase / Three phase  
Maximum power single phase (KW): 73.33  
Continuous power single phase (KW): 66.67  
Maximum power single phase (KVA): 91.67  
Continuous power single phase (KVA): 83.33  
Maximum power three phase (KW): 220  
Continuous power three phase (KW): 200  
Maximum power three phase (KVA): 275  
Continuous power three phase (KVA): 250  
Fuel: Diesel  
Frequency (Hz): 50  
Voltage (V): 230 / 400  
Sockets configuration: Terminal box  
Engine: Perkins 1206A-E70TTAG3  
Emissions Regulations: Stationary Use  
Engine rpm (rpm): 1500  
Speed governor: Electronic  
Starting system: Electric  
Engine capacity (cm<sup>3</sup>): 7010  
Number cylinders: 6  
Cooling: Water  
Alternator: Brushless  
Poles: 4  
Protection degree: IP44  
Bore x stroke (mm): 105 x 135  
Fuel tank capacity (L): 250  
Consumption (L/h): 41.5  
Running time (h): 6  
Length (mm): 2800  
Width (mm): 1310

Height (mm): 1800

Dry weight (Kg): 2115

Silenced: No

Super silenced: No

Product type: Generator

ATS Switch device : Optional

Voltage regulator: AVR

Engine manufacturer: Perkins