



# LUXTOWER LUX M11 PLUS LIGHT TOWER WITH FAST TOWING TROLLEY

**Product price:**

**9.322,00 € tax excluded**

**Product description:**

**LUXTOWER LUX M11PLUS LED LIGHT TOWER**

The LUXTOWER Lux M11PLUS Light Tower is the ideal solution for illuminating large areas, thanks to its advanced technology and the robustness of its components. Designed to ensure maximum energy efficiency, this light tower provides powerful and uniform illumination, making it perfect for construction sites, events, and industrial applications.

The LUXTOWER Lux M11PLUS is a compact and easily transportable light tower that can effectively illuminate areas up to 9300 sqm, with a reduced environmental impact.

Two versions available for every need:

The LUXTOWER Lux M11PLUS is available in two configurations:

Version L (Slow for Construction Sites) – Perfect for applications in enclosed spaces or with mobility restrictions.

Version V (Road Approved) – Suitable for road transport with all required safety standards.

The LUXTOWER Lux M11PLUS light tower is equipped with an 8-meter vertical telescopic mast with manual lifting and 4x320 W LED high-efficiency floodlights.

The LUXTOWER Lux M11PLUS light tower consists of a single-phase 3.5 KVA generator set powered by a Kubota Z482 diesel engine operating at 1500 rpm, enclosed in a soundproofed casing that makes it ultra-quiet.

INCLUDED WITH THE LUXTOWER Lux M11PLUS



- DSE3110 control panel
- Main / Generator selector
- Dusk sensor
- Liquid collection tank

**Technical Features of LUXTOWER Lux M11PLUS Light Tower:**

Projectors: 4 x 320 W LED

Illuminated Area: 9300 Sqm

Max Height: 8 m

Lifting: Manual

Engine: Kubota Z482

Maximum Single-Phase Power: 3.5 KVA

Emission Standard: STAGE V

Auxiliary Outlet: 1.3 KVA

Fuel: Diesel

Engine Speed: 1500 rpm

Max Wind Resistance: 80 km/h

Noise Level at 7 m: 65 dB (A)

Tank Capacity: 80 l

Autonomy: 145 h

Consumption: 0.55 l/h

Main / Generator Selector

Digital Control Panel DSE3110

Dusk Sensor

Liquid Collection Tank

If you are looking for other light towers like the LUXTOWER Lux M11PLUS, you can browse our full catalog dedicated to light towers from LUXTOWER or other brands.

Images and technical data are not binding.

**Product features:**

Phase: Single phase

Maximum power single phase (KVA): 3.5

Fuel: Diesel

Frequency (Hz): 50

Voltage (V): 230

Engine: Kubota Z482

Emissions Regulations: STAGE V

Engine rpm (rpm): 1500

Starting system: Elettrico

Number cylinders: 2

Cooling: Liquid





---

Alternator: Linz Synchronous or equivalent  
Maximum height (m): 8  
Type of lamps: LED  
Lamps: 4 x 320 W  
Telescopic pole: Vertical  
Illuminated area (m<sup>2</sup>): 9300  
Lifting System: Manual lifting system  
Mast rotation: 340°  
With generator / Without generator: With generator  
Stability to wind (Km/h): 80 Km/h  
Fuel tank capacity (L): 80  
Consumption (L/h): 0.55  
Running time (h): 145  
Acoustic pressure: 65 dB(A) at 7 m  
Silenced: Yes  
Super silenced: Yes  
Product type: Light tower  
Engine manufacturer: Kubota  
Auxiliary socket (kVA): 1.3  
Dimensioni min. (mm): L : 1780 X 1380 X 2560  
Dimensioni max. (mm): L : 2410 X 2520 X 8000  
Peso totale a secco (Kg): L (Traino lento) : 700

