



# LUXTOWER LUX M11 PLUS LIGHT TOWER WITH FAST TOWING TROLLEY

**Product price:**

**11.115,00 € tax excluded**

## **Product description:**

### LUXTOWER LUX M11 PLUS LIGHT TOWER WITH FAST TOWING TROLLEY

LUXTOWER LUX M11 PLUS is a compact and easily transportable light tower that can effectively illuminate areas up to 4700 square meters, with a reduced environmental impact.

LUXTOWER LUX M11 PLUS light tower is equipped with a 9 meters vertical telescopic pole with manual lifting and 4x300 W LED floodlights with high luminous efficiency.

The lighting tower LUXTOWER LUX M11 PLUS is composed of a single-phase generating set of 3.5 KVA equipped with Kubota Z482 engine powered by diesel at 1500 rpm and soundproof enclosure that makes it supersilenced.

LUXTOWER LUX M11 PLUS is supplied complete with fast towing trolley complete with autonomous braking system, complete with rear lights with integrated reverse light and all the features for a proper urban and extra-urban transport.

### OPTIONAL INCLUDED IN THE SUPPLY LUXTOWER LUX M11 PLUS

- DSE control system
- Generator network selector
- Twilight sensor
- Liquid collection tank

### TECHNICAL FEATURES LUXTOWER LUX M11 PLUS

Projectors: 4 X 320W LED

Lighted Area: 4700 Sq Ft

Max Height: 9 Mt



Lift: Manual  
Motor: Kubota Z482  
Maximum Single-Phase Power: 3.5 KVA  
Emissions Standard: STAGE V  
Power Supply: Diesel  
Engine RPM: 1500 rpm  
Telescopic Pole: Galvanized Steel  
Max Wind Resistance: 80 Km/h  
Transportation: Road Trailer  
Noise level at 7 mt: 65 dB (A)  
Tank Capacity: 80 l  
Runtime: 145 h  
Consumption: 0. 55 l/h  
Closed tower dimensions: 1800 X 1400 X 2600 mm  
Open tower dimensions: 2400 X 2500 X 8000 mm  
Dry weight: 700 Kg

If you are looking for more light towers like the LUXTOWER M11 then you can browse our entire catalog dedicated to beacon-towers of LUXTOWER or other brands.

Images and technical data are not binding.

**Product features:**

Phase: Single phase  
Maximum power single phase (KVA): 3.5  
Fuel: Diesel  
Frequency (Hz): 50  
Voltage (V): 230  
Engine: KUBOTA Z482  
Engine rpm (rpm): 1500  
Starting system: Electric  
Number cylinders: 2  
Cooling: Water  
Alternator: Linz Alumen SP-E1C  
Type of lamps: LED  
Lamps: 4 x 320 W  
Telescopic pole: Vertical  
Illuminated area (m<sup>2</sup>): 4700  
Lifting System: Manual lifting system  
Maximum height (m): 9  
Mast rotation: 340°  
Open size (mm): 2400 X 2500 X 8000

---

Lenght closed (mm): 1800  
Width closed (mm): 1400  
Height closed (mm): 2600  
With generator / Without generator: With generator  
Transportability: Fast Trailer  
Stability to wind (Km/h): 80 Km/h  
Fuel tank capacity (L): 80  
Consumption (L/h): 0.55  
Running time (h): 145  
Acoustic pressure: 65 dB(A) at 7 m  
Dry weight (Kg): 700  
Silenced: Yes  
Super silenced: Yes  
Product type: Light tower  
Engine manufacturer: Kubota