

# CGM 450P-C500 WITH MANUAL CONTROL PANEL



**Product price:**

**73.050,00 € tax excluded**

## **Product description:**

CGM 450P-C500 Single/three-phase 450KVA generator super-silenced with manual control panel

The CGM 450P-C500 is a single/three phase 450KVA generator with a 1500 rpm Perkins diesel engine, compact and easy to use, mounted on a fixed base. This generator is equipped with a soundproofed cabin made of structural steel plate, weatherproofing and an interior cladding made of sound-absorbing material with high noise reduction, which makes the CGM 450P-C500 supersilenced.

The CGM 450P-C500 generator consists of a Stamford, Mecc Alte or Marelli Motori, self-excited, brushless alternator with AVR voltage regulator. The CGM 450P-C500 generator is equipped with an electric starter with a low fuel consumption battery, consuming only 72 litres per hour at 75% load. The fuel tank is incorporated in the crankcase for ease of use.

This generator is perfect for use outdoors, such as on construction sites.

The CGM 450P-C500 generator is part of the Industrial range and is characterised by its versatility for installation in urban environments such as shops or shopping centres, for the telecommunications environment, for military applications and much more.

## **Technical characteristics of the CGM 450P-C500 generator:**

Phase type: Single-phase / Three-phase

Maximum three-phase power: 396 KW / 495 KVA

Three-phase continuous power: 360 KW / 450 KVA

Maximum single-phase power: 132 KW / 165 KVA

Single-phase continuous use power: 120 KW / 150 KVA

Fuel: Diesel

Voltage: 230 V / 400 V

Frequency: 50 Hz

Motor: PERKINS 2506A-E15TAG1

Engine speed: 1500 rpm

Starting: Electric



Consumption: 72 Lt/h at 75% load  
Length: 4850 mm  
Width: 1850 mm  
Height: 2550 mm  
Weight: 5080 Kg  
Super-silenced  
AVR

If you are looking for a product like the CGM 450P-C500 then you can browse the full range of CGM generators or other types of products in our catalogue to find the one that best suits your needs.

Images and technical data are not binding.

#### **Product features:**

Phase: Single phase / Three phase  
Maximum power single phase (KW): 132  
Continuous power single phase (KW): 120  
Maximum power single phase (KVA): 165  
Continuous power single phase (KVA): 150  
Maximum power three phase (KW): 396  
Continuous power three phase (KW): 360  
Maximum power three phase (KVA): 495  
Continuous power three phase (KVA): 450  
Fuel: Diesel  
Frequency (Hz): 50  
Voltage (V): 230 / 400  
Sockets configuration: Terminal box  
Engine: Perkins 2506A-E15TAG1  
Emissions Regulations: Stationary Use  
Engine rpm (rpm): 1500  
Speed governor: Electronic  
Starting system: Electric  
Engine capacity (cm<sup>3</sup>): 15200  
Number cylinders: 6  
Cooling: Water  
Alternator: Brushless  
Poles: 4  
Protection degree: IP44  
Bore x stroke (mm): 137 x 171  
Fuel tank capacity (L): 400  
Consumption (L/h): 72



---

Running time (h): 5.6  
Acoustic pressure: 69 dB(A) at 7 m  
Length (mm): 4850  
Width (mm): 1850  
Height (mm): 2550  
Dry weight (Kg): 5080  
Silenced: Yes  
Super silenced: Yes  
Product type: Generator  
ATS Switch device : No  
Voltage regulator: AVR  
Engine manufacturer: Perkins