



# TELAIR DUALCLIMA 12500H AIR CONDITIONER WITH HEAT PUMP 10800 BTU

**Product price:**

**1.600,00 € tax excluded**

## **Product description:**

TELAIR DUALCLIMA 12500H AIR CONDITIONER WITH HEAT PUMP 10800 BTU

TELAIR DUALCLIMA 12500H monoblock air conditioner with heat pump designed specifically for installation on the roof of medium and large motorhomes and caravans. Particular care has been taken to ensure that the TELAIR DUALCLIMA 12500H is silent both inside and outside.

The TELAIR DUALCLIMA 12500H is equipped with a super flat diffuser with a profile that degrades on all 4 sides.

Front and rear air outlets that can be oriented both laterally and tangentially are present in the TELAIR DUALCLIMA 12500H.

## THE TECHNICAL FEATURES TELAIR DUALCLIMA 12500H

Cooling capacity: 10.800 BTU / 3,17 KW

Heating capacity: 10.500 BTU / 3,08 kW

Ventilation speed: 3 + AUTO

Average input power for cooling: 6.1 A

Average input power for heating: 5.9 A

Installation current: 29 A (150 m sec. )

Cooling power input: 1400W

Heating power input: 1350W

Generator needed: 2200W

Voltage: 230 V

Frequency: 50 Hz

Maximum airflow: 480 m3/h

Length: 239 mm

Width: 980 mm

Height: 650 mm



Weight: 39 kg

The high-efficiency heat pump of the TELAIR DUALCLIMA 12500H provides high heating power with less than half the power consumption delivered. The heat pump is effective for outdoor temperatures up to 4°C; below this value, the power is drastically reduced.

### Automatic control

By activating the AUTO function, the TELAIR DUALCLIMA 12500H automatically selects the most appropriate fan speed and cooling or heating function.

- Remote control with programmable timer and ON/OFF button diffuser lights
- Anti-icing protection probes
- Replaceable and washable internal filters
- Suitable for roofs with thickness from 30 to 70 mm

Are you looking for an air conditioner with different technical characteristics? Here you can find the area dedicated to air conditioners TELAIR or other specialized brands

Images and technical data are not binding and may be subject to revision by the supplier.

### Product features:

Frequency (Hz): 50

Voltage (V): 230

Refrigerating yield: 10.800 BTU / 3,17 KW

Heating power: 10.500 BTU / 3,08 kW

Ventilation speeds: 3 + AUTO

Courant de démarrage (A): 29

Absorbed average current, refrigerating (A): 6.1

Absorbed average current, heater (A): 5.9

Inlet power, refrigerating (KW): 1.4

Inlet power, heater (KW): 1.35

Maximum air flow rate (m<sup>3</sup>/h): 480

Air diffuser height (cm): 4.9

Length (mm): 980

Width (mm): 239

Height (mm): 650

Type of climate control: Roof Air Conditioner

Recommended vehicle length (m): 7

Product type: Air conditioner

Weight (Kg): 39