

GENERATOR SINGLE- PHASE/THREE-PHASE 143 KVA AVR



Product price:

24.896,00 € tax excluded

Product description:

GENERATOR SINGLE-PHASE/ THREE-PHASE POWER 143 KVA AVR

Generator set 143KVA single-phase/three-phase with FPT engine powered by diesel at 1500 rpm, compact and easy to use, mounted on a fixed base. This generator is equipped with a soundproof cabin made of structural steel sheet, weatherproof and internal lining of soundproofing material with high noise reduction that make it **supersilenced**.

The generator set consists of a Stamford, Mecc Alte or Marelli Motori alternator, self-excited, brushless and with **AVR** voltage regulator. The generator set is equipped with electric start with battery with a low fuel consumption in fact it consumes only 28 liters/hour at 75% of the load. In addition to this, it has a panel with an automatic control unit and a terminal board for automatic start-up.

This generator set is perfect for outdoor use such as for shipbuilding use.

TECHNICAL FEATURES

Phase type: Single phase / Three phase

Maximum three phase power: 143 KVA / 114.4 KW

Three phase continuous use power: 130 KVA / 104 KW

Maximum single phase power: 47.6 KVA / 38 KW

Maximum single phase continuous use power: 43.3 KVA / 34.5 KW

Fuel: Diesel

Voltage: 230/400 V

Frequency: 50 Hz

Motor: FPT NEF67 TM4

Motor speed: 1500 rpm

Voltage regulator: AVR

Start: Electric

Tank capacity: 230 l



Consumption: 29.4L/h
Length: 3400 mm
Width: 1100 mm
Height: 1820 mm
Weight: 1850 Kg
Super silenced

Are you looking for a generator set with different technical characteristics? Here you can find the full range or other brands specializing in the field.

The images are purely indicative.

Product features:

Phase: Single phase / Three phase
Maximum power single phase (KW): 38
Continuous power single phase (KW): 34.5
Maximum power single phase (KVA): 47.6
Continuous power single phase (KVA): 43.3
Maximum power three phase (KW): 114.4
Continuous power three phase (KW): 104
Maximum power three phase (KVA): 143
Continuous power three phase (KVA): 130
Fuel: Diesel
Frequency (Hz): 50
Voltage (V): 230 / 400
Sockets configuration: Terminal box
Engine: FPT NEF67 TM4
Emissions Regulations: Stationary Use
Engine rpm (rpm): 1500
Starting system: Electric
Engine capacity (cm³): 4500
Number cylinders: 4
Cooling: Water
Alternator: Synchronous
Protection degree: IP23
Motor insulation class: H
Fuel tank capacity (L): 230
Consumption (L/h): 29.4
Acoustic power: 95 dB(A)
Acoustic pressure: 70 dB(A) at 7 m
Length (mm): 3400
Width (mm): 1100



Height (mm): 1820
Dry weight (Kg): 1850
Silenced: Yes
Super silenced: Yes
Product type: Generator
ATS Switch device : Yes
Voltage regulator: AVR
Engine manufacturer: FPT Iveco