

# GENSET MG 10001 SS-K SINGLE-PHASE GENERATOR 10KVA



**Product price:**

**6.165,50 € tax excluded**

## Product description:

GENSET MG 10001 SS-K SINGLE-PHASE GENERATOR 10KVA

GENSET MG 10001 SS-K Singlephase generator with Kubota D722 StageV engine powered by diesel, capable of delivering a maximum power of 10KVA.

The GENSET MG 10001 SS-K is compact and easy to use, equipped with an enclosure that lowers noise emissions and makes it super-silenced.

The GENSET MG 10001 SS-K is a single-phase 10KVA diesel generator set with electric start. This generator is also available with an automatic panel and remote control.

The GENSET MG 10001 SS-K generator, thanks to the high quality and efficiency of its components, is ideal for various types of work: from small hobby work to large construction sites.

The GENSET MG 10001 SS-K generator set includes:

- Automatic engine stop device with warning lights for:
  - battery charge failure
  - high water temperature
  - low fuel level
  - low oil pressure
- 12V built-in battery
- 1 singlephase EEC 230V - 32A
- 1 singlephase EEC 230V - 16A
- 1 singlephase Schuko 230V - 16A
- output protections
- Earth leakage circuit breaker
- Emergency stop button
- Fuel level indicator

- Hour meter
- Central lifting hook
- Arrangement for AMF-ATS or Remote control

#### TECHNICAL FEATURES GENSET MG 10001 SS-K

Phase Type: SinglePhase  
Maximum SinglePhase Power: 10KVA / 8 KW  
Continuous SinglePhase Power: 9 KVA / 7.2 KW  
VAC Voltage: 230 V  
Frequency (Hz): 50  
Starting Frame: Electric  
Motor: Kubota D722  
Emission Standard: Stage V  
RPM: 3000  
Supply: Diesel  
Fuel tank capacity: 30 l  
Consumption @ 75 % load: 3.3 l/h  
Autonomy @ 75 % load: 9.09 h  
Acoustic pressure: 95 dB(A)  
Length: 1360 mm  
Width: 675 mm  
Height: 860 mm  
Net weight: 300 Kg

Are you looking for a generator with different technical characteristics? Here you can find the full range of GENSET or other specialized brands

Images and technical data are not binding and may be subject to revision by the manufacturer.

#### **Product features:**

Phase: Single phase  
Maximum power single phase (KW): 8  
Continuous power single phase (KW): 7.2  
Maximum power single phase (KVA): 10  
Continuous power single phase (KVA): 9  
Fuel: Diesel  
Frequency (Hz): 50  
Voltage (V): 230  
Sockets configuration: 1 x 230V 16A CEE - 1 x 230V 32A CEE - 1 x 230V 16A SCHUKO  
Engine: Kubota D722  
Emissions Regulations: Stage 5

---

Engine rpm (rpm): 3000  
Starting system: Electric  
Engine capacity (cm<sup>3</sup>): 719  
Number cylinders: 3  
Cooling: Water  
Alternator: Synchronous  
Protection degree: IP23  
Motor insulation class: H  
Fuel tank capacity (L): 30  
Consumption (L/h): 3.3  
Running time (h): 9.09  
Acoustic power: 95 dB(A)  
Acoustic pressure: 70 dB(A) at 7 m  
Length (mm): 1360  
Width (mm): 674  
Height (mm): 860  
Dry weight (Kg): 300  
Silenced: Yes  
Super silenced: Yes  
Product type: Generator  
ATS Switch device : Optional  
Voltage regulator: No  
Engine manufacturer: Kubota