



GENSET MG 10/8 SS-KL SINGLE-PHASE / THREE- PHASE GENERATOR 10KVA

Product description:

GENSET MG 10/8 SS-KL SINGLE-PHASE / THREE-PHASE GENERATOR 10KVA

GENSET MG 10/8 SS-KL is a single-phase / three-phase generating set equipped with a Kubota D1105 (STAGE V) Diesel engine, capable of delivering a maximum power of 10KVA.

The GENSET MG 10/8 SS-KL generator set provides reliable power for home, business and recreational environments, safely powering appliances and other electronic devices.

The genset is as easy to install and operate as it is to start and stop with clear, intuitive controls. The GENSET MG 10/8 SS-KL is powered by a Kubota D1105 **STAGE V** Diesel engine. They are very reliable engines that guarantee efficient combustion and low fuel consumption, they are also equipped with a protection system that causes the engine to stop if the oil level is too low.

The GENSET MG 10/8 SS-KL has an all-steel construction and a large metal tank. The generator set guarantees an efficient and silent operation thanks to the Kubota D1105 which allows to deliver a maximum power of 10 KVA.

The generator set is supplied with:

- Battery 12 V
- 1 threephase socket CEE 400V - 16A
- 1 singlephase socket CEE 230V - 32A
- 1 singlephase socket CEE 230V - 16A
- Thermal protector
- Differential switch
- Emergency stop button
- Voltage selector

- Voltmeter
- Hour meter
- Central lifting hook
- Arrangement for operation in AMF-ATS or Remote control
- Glow plugs preheating warning light
- Automatic engine stop device with warning lights for:
 - battery failure
 - high water temperature
 - low oil pressure
 - low fuel level

TECHNICAL SPECIFICATIONS GENSET MG 10/8 SS-KL

Phase Type: SinglePhase/ThreePhase
Maximum SinglePhase Power: 6 KVA / 4.8 KW
Maximum ThreePhase Power: 10 KVA / 8 KW
VAC Voltage: 230 / 400 V
Frequency (Hz): 50
Quadro Starter: Electric
Motor: Kubota D1105
Emission Standard: Stage V
RPM: 1500
Power supply: Diesel
Fuel tank capacity: 30 l
Consumption @ 75 % load: 2 l/h
Autonomy @ 75 % load: 15 h
Sound pressure: 90 dB(A)
Length: 1360 mm
Width: 675 mm
Height: 860 mm
Net weight: 350 kg

Are you looking for a generator set with different characteristics? Here you can find the full range of GENSET products or other brands specializing in the field

Images and technical data are not binding and may be subject to revision by the supplier.

Product features:

Phase: Single phase / Three phase
Maximum power single phase (KW): 4.8
Maximum power single phase (KVA): 6
Maximum power three phase (KW): 8



Maximum power three phase (KVA): 10

Fuel: Diesel

Frequency (Hz): 50

Voltage (V): 230 / 400

Sockets configuration: 1 x 400V 16A CEE - 1 x 230V 16A CEE - 1 x 230V 32A CEE

Engine: Kubota D1105

Emissions Regulations: Stage 5

Engine rpm (rpm): 1500

Starting system: Electric

Engine capacity (cm³): 1123

Number cylinders: 3

Cooling: Water

Alternator: Synchronous

Protection degree: IP23

Motor insulation class: H

Fuel tank capacity (L): 30

Consumption (L/h): 2

Running time (h): 15

Acoustic power: 90 dB(A)

Acoustic pressure: 65 dB(A) at 7 m

Length (mm): 1360

Width (mm): 675

Height (mm): 860

Dry weight (Kg): 350

Silenced: Yes

Super silenced: Yes

Product type: Generator

ATS Switch device : Optional

Voltage regulator: No

Engine manufacturer: Kubota

