



# CGM 375S-B400 WITH AUTOMATIC CONTROL PANEL



**Product price:**

**41.963,00 € tax excluded**

## **Product description:**

CGM 375S-B400 Single/three-phase 375KVA generator with automatic control panel

The CGM 375S-B400 is a single/three phase 375KVA generator with a 1500 rpm Scania diesel engine, compact and easy to use, mounted on a fixed base. This CGM 375S-B400 generator is in an open version and is easy to handle and transport thanks to its base with pivoting feet.

The CGM 375S-B400 generator consists of a Stamford, Mecc Alte or Marelli Motori, self-excited, brushless alternator with AVR voltage regulator. The CGM 375S-B400 generator is equipped with an electric starter with a low fuel consumption battery, consuming only 54 litres per hour at 75% load. In addition, it has a control panel with automatic control unit and terminal box for automatic start-up.

This generator is perfect for use outdoors, such as on construction sites.

The CGM 375S-B400 generator is part of the Industrial range and is characterised by its versatility for installation in urban environments such as shops or shopping centres, for the telecommunications environment, for military applications and much more.

## **Technical characteristics of the CGM 375S-B400 generator:**

Phase type: Single-phase / Three-phase

Maximum three-phase power: 330 KW / 412.5 KVA

Three-phase continuous power: 300 KW / 375 KVA

Maximum single-phase power: 110 KW / 137.5 KVA

Single-phase continuous use power: 100 KW / 125 KVA

Fuel: Diesel

Voltage: 230 V / 400 V

Frequency: 50 Hz

Motor: SCANIA DC13 072A 02 11

Engine speed: 1500 rpm

Starting: Electric

Consumption: 54 Lt/h at 75% load

Length: 2950 mm



Width: 1550 mm  
Height: 2100 mm  
Weight: 3230 Kg  
AVR

If you are looking for a product like the CGM 375S-B400 then you can browse the full range of CGM generators or other types of products in our catalogue to find the one that best suits your needs.

Images and technical data are not binding.

**Product features:**

Phase: Single phase / Three phase  
Maximum power single phase (KW): 110  
Continuous power single phase (KW): 100  
Maximum power single phase (KVA): 137.5  
Continuous power single phase (KVA): 125  
Maximum power three phase (KW): 330  
Continuous power three phase (KW): 300  
Maximum power three phase (KVA): 412.5  
Continuous power three phase (KVA): 375  
Fuel: Diesel  
Frequency (Hz): 50  
Voltage (V): 230 / 400  
Sockets configuration: Terminal box  
Engine: Scania DC13 072A 02 11  
Emissions Regulations: Stationary Use  
Engine rpm (rpm): 1500  
Speed governor: Electronic  
Starting system: Electric  
Engine capacity (cm<sup>3</sup>): 12700  
Number cylinders: 6  
Cooling: Water  
Alternator: Brushless  
Poles: 4  
Protection degree: IP44  
Bore x stroke (mm): 130 x 160  
Fuel tank capacity (L): 400  
Consumption (L/h): 54  
Running time (h): 7.4  
Width (mm): 1550  
Height (mm): 2100

Dry weight (Kg): 3230

AVR: Yes

Silenced: No

Super silenced: No

Product type: Generator

ATS Switch device : Optional

Voltage regulator: AVR

Engine manufacturer: Scania