



CGM DUAL20000SP THREE-PHASE GENERATOR 20,7KVA AVR STAGE V

Product price:

3.202,50 € tax excluded

Product description:

CGM DUAL20000SP THREE-PHASE GENERATOR 20,7KVA AVR STAGE V

The CGM DUAL20000SP single-phase / three-phase Generator is equipped with OHV1000 Stage V gasoline engine, capable of delivering a power of 20,7KVA, complete with **Voltage regulator AVR**.

The CGM DUAL20000SP adapts perfectly to the most varied uses, thanks to the handling trolley that allows you to relocate it in perfect safety and simplicity. Thanks to the oversized 65-liter tank, this generator has an extraordinary autonomy of 6.6 hours at 75% load.

These CGM DUAL20000SP are equipped with high quality components, lightweight, compact, ease of use and also modern design, equipped with a practical electric start.

The alternator of CGM DUAL20000SP is synchronous, single-phase, self-excited, self-regulated, brushless with class H insulation and AVR regulator.

The advantages of AVR voltage regulator

The automatic voltage regulator, or AVR allows the CGM DUAL20000SP to deliver stable energy and then be able to connect equipment with delicate electronics such as computers, appliances, smartphones and tablets: the generator is therefore ideal for use at home, camping, hobby and leisure, but also for construction sites and craftsmen.

TECHNICAL FEATURES CGM DUAL20000SP

Phase Type: SinglePhase / ThreePhase

Maximum SinglePhase Power: 20.7 KVA / 16.5 KW



Maximum ThreePhase Power: 20.7 KVA / 16.5KW
Voltage: 230 / 400 V
Frequency: 50 Hz
Motor: OHV1000
Fuel: Gasoline
Motor RPM: 3000 rpm
Emission Standard: Stage V
Number of cylinders: 2
Displacement: 999 cc
Fuel tank capacity: 65 l
Consumption: 9.8 l @ 75%
Autonomy: 6.6 h
Alternator: Self-excited Brushless
Voltage regulator: AVR
Socket configuration: 1 x schuko - 1 x 63A 3P 230V - 1 x 32A 5P 400V - 1 x 12 VDC
Width: 970 mm
Length: 680 mm
Height: 955 mm
Dry weight: 255 Kg

Are you looking for a generator with different technical characteristics? Here you can find the full range of CGM generators or other specialized brands

Images and technical data are not binding.

Product features:

Phase: Single phase / Three phase
Maximum power single phase (KW): 16.5
Maximum power single phase (KVA): 20,7
Maximum power three phase (KW): 16,5
Maximum power three phase (KVA): 20,7
Fuel: Gasoline
Frequency (Hz): 50
Voltage (V): 230 / 400
Sockets configuration: 1 x schuko - 1 x 63A 3P 230V - 1 x 32A 5P 400V - 1 x 12 VDC
Engine: OHV1000
Emissions Regulations: Stage 5
Engine rpm (rpm): 3000
Starting system: Electric
Engine capacity (cm³): 999
Number cylinders: 2
Alternator: Self-excited Brushless



Fuel tank capacity (L): 65
Consumption (L/h): 9.8 l @ 75%
Running time (h): 6.6 at 75% of the load
Length (mm): 970
Width (mm): 680
Height (mm): 955
Dry weight (Kg): 255
Silenced: No
Super silenced: No
Product type: Generator
ATS Switch device : No
Voltage regulator: AVR
Engine manufacturer: CGM

