



CGM DUAL15000SP THREE-PHASE GENERATOR 15KVA AVR STAGE V

Product price:

1.747,00 € tax excluded

Product description:

CGM DUAL15000SP THREE-PHASE GENERATOR 15KVA AVR STAGE V

The CGM DUAL15000SP single-phase / three-phase Generator is equipped with OHV720 Stage V gasoline engine, capable of delivering a power of 15KVA, complete with **Voltage regulator AVR**.

The CGM DUAL15000SP adapts perfectly to the most varied uses, thanks to the handling trolley that allows you to relocate it in perfect safety and simplicity. Thanks to the oversized 40 liter tank, this generator has an extraordinary autonomy of 8,2 hours at 75% load.

These CGM DUAL15000SP are equipped with high quality components, lightweight, compact, ease of use and also modern design, equipped with a practical electric start.

The alternator of CGM DUAL15000SP is synchronous, single-phase, self-excited, self-regulated, brushless with class H insulation and AVR regulator.

The advantages of AVR voltage regulator

The automatic voltage regulator, or AVR allows the CGM DUAL15000SP to deliver stable energy and then be able to connect equipment with delicate electronics such as computers, appliances, smartphones and tablets: the generator is therefore ideal for use at home, camping, hobby and leisure, but also for construction sites and craftsmen.

TECHNICAL FEATURES CGM DUAL15000SP

Phase Type: Singlephase / Threephase
Singlephase Maximum Power: 13,8 KVA / 11 KW



Threephase Maximum Power: 15 KVA / 12 KW

Voltage: 230 / 400 V

Frequency: 50 Hz

Engine: OHV720

Fuel: Gasoline

Engine RPM: 3000 rpm

Emissions Standard: Stage V

Number of cylinders: 2

Displacement: 713 cc

Fuel tank capacity: 40 l

Fuel consumption: 4.9 l @ 75%

Range: 8.2 h

Alternator: Self-excited with brushes

Receptacle configuration: 2 x 32A 3P 230V - 1 x 32A 5P 400V - 1 x 12 VDC

Voltage regulator: AVR

Width: 870 mm

Length: 588 mm

Height: 726 mm

Dry weight: 184 Kg

Are you looking for a generator with different technical characteristics? Here you can find the full range of CGM generators or other specialized brands

Images and technical data are not binding.

Product features:

Phase: Single phase / Three phase

Maximum power single phase (KW): 11

Maximum power single phase (KVA): 13.8

Maximum power three phase (KW): 12

Maximum power three phase (KVA): 15

Fuel: Gasoline

Frequency (Hz): 50

Voltage (V): 230 / 400

Sockets configuration: 2 x 32A 3P 230V - 1 x 32A 5P 400V - 1 x 12 VDC

Engine: OHV720

Emissions Regulations: Stage 5

Engine rpm (rpm): 3000

Starting system: Electric

Engine capacity (cm³): 713

Number cylinders: 2

Alternator: Self-excited with brushes

Fuel tank capacity (L): 40

Consumption (L/h): 4.9 l @ 75%

Running time (h): 8.2 at 75% of the load

Length (mm): 870

Width (mm): 588

Height (mm): 726

Dry weight (Kg): 184

Silenced: No

Super silenced: No

Product type: Generator

ATS Switch device : No

Voltage regulator: AVR

Engine manufacturer: CGM