



# CGM DUAL15000SP THREE-PHASE GENERATOR 15KVA AVR STAGE V

Product price:

**1.747,00 € tax excluded**

## Product description:

CGM DUAL15000SP THREE-PHASE GENERATOR 15KVA AVR STAGE V

The CGM DUAL15000SP single-phase / three-phase Generator is equipped with OHV720 Stage V gasoline engine, capable of delivering a power of 15KVA, complete with **Voltage regulator AVR**.

The CGM DUAL15000SP adapts perfectly to the most varied uses, thanks to the handling trolley that allows you to relocate it in perfect safety and simplicity. Thanks to the oversized 40 liter tank, this generator has an extraordinary autonomy of 8,2 hours at 75% load.

These CGM DUAL15000SP are equipped with high quality components, lightweight, compact, ease of use and also modern design, equipped with a practical electric start.

The alternator of CGM DUAL15000SP is synchronous, single-phase, self-excited, self-regulated, brushless with class H insulation and AVR regulator.

The advantages of AVR voltage regulator

The automatic voltage regulator, or AVR allows the CGM DUAL15000SP to deliver stable energy and then be able to connect equipment with delicate electronics such as computers, appliances, smartphones and tablets: the generator is therefore ideal for use at home, camping, hobby and leisure, but also for construction sites and craftsmen.

TECHNICAL FEATURES CGM DUAL15000SP

Phase Type: Singlephase / Threephase  
Singlephase Maximum Power: 13,8 KVA / 11 KW



---

Threephase Maximum Power: 15 KVA / 12 KW  
Voltage: 230 / 400 V  
Frequency: 50 Hz  
Engine: OHV720  
Fuel: Gasoline  
Engine RPM: 3000 rpm  
Emissions Standard: Stage V  
Number of cylinders: 2  
Displacement: 713 cc  
Fuel tank capacity: 40 l  
Fuel consumption: 4.9 l @ 75%  
Range: 8.2 h  
Alternator: Self-excited with brushes  
Receptacle configuration: 2 x 32A 3P 230V - 1 x 32A 5P 400V - 1 x 12 VDC  
Voltage regulator: AVR  
Width: 870 mm  
Length: 588 mm  
Height: 726 mm  
Dry weight: 184 Kg

Are you looking for a generator with different technical characteristics? Here you can find the full range of CGM generators or other specialized brands

Images and technical data are not binding.

**Product features:**

Phase: Single phase / Three phase  
Maximum power single phase (KW): 11  
Maximum power single phase (KVA): 13.8  
Maximum power three phase (KW):  
Maximum power three phase (KVA):  
Fuel: Gasoline  
Frequency (Hz): 50  
Voltage (V): 230 / 400  
Sockets configuration: 2 x 32A 3P 230V - 1 x 32A 5P 400V - 1 x 12 VDC  
Engine: OHV720  
Emissions Regulations: Stage 5  
Engine rpm (rpm): 3000  
Starting system: Electric  
Engine capacity (cm<sup>3</sup>): 713  
Number cylinders: 2  
Alternator: Self-excited with brushes

Fuel tank capacity (L): 40

Consumption (L/h): 4.9 l @ 75%

Running time (h): 8.2 at 75% of the load

Length (mm): 870

Width (mm): 588

Height (mm): 726

Dry weight (Kg): 184

Silenced: No

Super silenced: No

Product type: Generator

ATS Switch device : No

Voltage regulator: AVR

Engine manufacturer: CGM