



# CGM 40KH-C50 WITH MANUAL CONTROL PANEL

## Product description:

CGM 40KH-C50 Single/three-phase 40KVA generator super-silenced with manual control panel

The CGM 40KH-C50 is a single/three phase 40KVA generator with a 1500 rpm Kohler diesel engine, compact and easy to use, mounted on a fixed base. This generator is equipped with a soundproofed cabin made of structural steel plate, weatherproofing and an interior lining of soundproofing material with high noise reduction, which makes the CGM 40KH-C50 super-silenced.

The CGM 40KH-C50 generator consists of a Stamford, Mecc Alte or Marelli Motori, self-excited, brushless alternator with AVR voltage regulator. The CGM 40KH-C50 generator is equipped with an electric starter with a low fuel consumption battery, consuming only 7,5 litres per hour at 75% load. The fuel tank is incorporated in the crankcase for ease of use.

This generator is perfect for use outdoors, such as on construction sites.

The CGM 40KH-C50 generator is part of the Industrial range and is characterised by its versatility for installation in urban environments such as shops or shopping centres, for the telecommunications environment, for military applications and much more.

## Technical characteristics of the CGM 40KH-C50 generator:

Phase type: Single-phase / Three-phase

Maximum three-phase power: 35.2 KW / 44 KVA

Three-phase continuous power: 32 KW / 40 KVA

Maximum single-phase power: 11.73 KW / 14.67 KVA

Single-phase continuous use power: 10.67 KW / 13.33 KVA

Fuel: Diesel

Voltage: 230 V / 400 V

Frequency: 50 Hz

Motor: KOHLER KDI 2504TM-40

Engine speed: 1500 rpm

Starting: Electric

Consumption: 7.5 Lt/h at 75% load



Length: 2000 mm  
Width: 850 mm  
Height: 1275 mm  
Weight: 840 Kg  
Super-silenced  
AVR

If you are looking for a product like the CGM 40KH-C50 then you can browse the full range of CGM generators or other types of products in our catalogue to find the one that best suits your needs.

Images and technical data are not binding.

**Product features:**

Phase: Single phase / Three phase  
Maximum power single phase (KW): 11.7  
Continuous power single phase (KW): 10.6  
Maximum power single phase (KVA): 14.6  
Continuous power single phase (KVA): 13.3  
Maximum power three phase (KW): 35.2  
Continuous power three phase (KW): 32  
Maximum power three phase (KVA): 44  
Continuous power three phase (KVA): 40  
Fuel: Diesel  
Frequency (Hz): 50  
Voltage (V): 230 / 400  
Sockets configuration: 1 X 400V 63A 5P CEE - 1 X 230V 16A 3P CEE  
Engine: Kohler KDI 2504TM-40  
Emissions Regulations: Stationary Use  
Engine rpm (rpm): 1500  
Speed governor: Mechanical  
Starting system: Electric  
Engine capacity (cm<sup>3</sup>): 2482  
Number cylinders: 4  
Cooling: Water  
Alternator: Brushless  
Poles: 4  
Protection degree: IP44  
Bore x stroke (mm): 88 x 102  
Fuel tank capacity (L): 100  
Consumption (L/h): 7.5  
Running time (h): 13.3



---

Acoustic pressure: 69 dB(A) at 7 m  
Length (mm): 2000  
Width (mm): 850  
Height (mm): 1275  
Dry weight (Kg): 840  
AVR: Yes  
Silenced: Yes  
Super silenced: Yes  
Product type: Generator  
ATS Switch device : No  
Voltage regulator: AVR  
Engine manufacturer: Kohler